

FORMULA
Use 922 HIGH FLASHPOINT
 LOW ODOR FORMULA
 RINSES WITH WATER

FORMULA
Or 207 LOW ODOR
 FAST-ACTING
 REMOVES CURED GLUES

- For best results, use our products at room temperature, read all instructions before using and test in a small area first.
- When used in accordance with the directions for use, our products will safely remove most urethane and other wood flooring adhesives, leaving a clean surface that is ready for recoating, staining, or new adhesives.
- Refer to the installation instructions for any new product being applied after using our products to determine necessary dry times and other surface preparation requirements. As always, feel free to contact Sentinel with any additional questions that you may have.

For best results, use the information below in combination with the directions for use on the product label or the technical data sheet.

Step 1 - Extreme example showing cured urethane adhesive on a pre-finished wood floor.



Typical finger or footprints will be less extreme.



Soak times will vary based on the type and amount of glue.

Step 2 - Sentinel Remover applied directly to cured adhesive and allowed to penetrate and soak for 40-60 minutes.

Step 3 - After soaking, adhesive is worked free from flooring using a 2" plastic putty knife.



Our products will not harm the finish on floors.

You may proceed directly to Step 4 if your adhesive is too light to require scraping.



Softened adhesive and remover is scraped from flooring.



Caution: Overscrubbing a matte finish floor could cause shiny spots, so take care if you have a matte finish floor.

Step 4 - After bulk of adhesive has been removed, flooring is scrubbed with a melamine pad to remove remaining adhesive residue .



Spray-on

Step 5 - Once all of the adhesive is removed, flooring is sprayed with Sentinel 810 All-Surface Floor Cleaner to remove any remaining adhesive remover and to clean and shine the flooring.*



This step is critical, so make sure all residue is removed.



Floors can be walked on as soon as they are dry.

With removal completed, you can see the cleaned area in contrast to the area that still has adhesive on it.

** In the event that you do not have access to Sentinel 810, a similar floor cleaner can be used. You may also use warm soapy water as well. The key is to soak up any remaining adhesive remover.*

As always, feel free to contact our technical support staff at 800-373-0633 with any questions that you might have.

Sentinel Products, Inc.
 51 NE 77th Avenue
 Minneapolis MN 55432
 800-373-0633 or www.senpro.com



HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

Visit www.senpro.com to view technical data sheets and Material Safety Data Sheets for all of our products.