

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

# PAINT & VARNISH

# STRIPPER<sub>gel</sub>

FORMULA

# 205

NON-TOXIC  
PLANT-DERIVED FORMULA  
CONTRACTOR STRENGTH  
AMAZINGLY QUICK & EASY

## PRODUCT DESCRIPTION:

SENTINEL 205 EZ-STRIP PAINT & VARNISH STRIPPER is an non-toxic, environmentally-safe stripper, powerful enough to dissolve virtually any finish. 205 is made with non-hazardous and plant-derived actives, making it an effective and safe alternative to products containing harmful agents. 205's thick, clear gel allows for easy use, especially on vertical surfaces and it rinses with water, making clean-up a breeze. The low-odor, nonflammable formula make it perfect for both indoor and outdoor projects. DO NOT USE ON PLASTIC OR FIBERGLASS.

## DIRECTIONS: (Always follow product label instructions for best results.)

Before use, read all instructions. Shake well before use and product will pour easier. Cover all adjacent surfaces to protect them from incidental contact with 205.

1. Squeeze/pour 205 onto the surface being stripped and spread with a rag or a paint brush. For best results, apply a generous amount of 205 to surface.
2. Let 205 penetrate the coating being removed. Times will vary based on thickness of coating. Varnish, shellac, and lacquer: 15-30 minutes. Latex/oil-based paints, polyurethane, and multi-layered finishes: 15 - 60+ minutes. For difficult to remove, multi-layered coatings, allow 205 to penetrate overnight.
3. Test scrape a small area of the surface with a putty knife to see if finish has softened. If not, let continue to soak.
4. Remove 205 and softened coating immediately after coating has softened by gently scraping with putty knife/ stripper tool. If removing multiple layers and surface remains grimy, a second application of 205 may be necessary.
5. Remove any remaining softened finish with a stripper pad dampened with soapy water. Always rub in the direction of the grain. Remove any leftover residue with a stripper pad dampened with water or mineral spirits.
6. Wipe surface with a dry, clean cloth. Let wood dry thoroughly (at least 24 hours) before refinishing.



See reverse side for  
Material Safety Data Sheet (MSDS)

**REMOVAL OF LEAD-BASED PAINT:** Only appropriately trained professionals should remove lead-based paint. Dispose of lead-based paint residue in accordance with federal, state, & local guidelines.

For additional information or assistance with this product, please call Sentinel Customer Service at, **800-373-0633**.

800-373-0633  
www.senpro.com

Sentinel Products, Inc  
51 NE 77th Ave  
Minneapolis MN 55432

MATERIAL SAFETY DATA SHEET

Sentinel Product Company, Inc. - 51 Northeast 77th Avenue, Minneapolis, MN 55432 (763)571-0630 – Fax(763)571-1819

**SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION**

PRODUCT NAME: SENTINEL 205 PAINT STRIPPER  
SYNONYMS: DETERGENT  
EMERGENCY/MEDICAL NUMBER: 1-866-359-5661

**SECTION 2 COMPONENT & EXPOSURE DATA**

COMPONENT	CAS#	PEL	TLV
Ethyl hydroxy proprionate	97-64-3	NE	NE

**SECTION 3 EMERGENCY AND FIRST AID PROCEDURES**

EYE CONTACT: If this product comes in contact with eyes, gently flush with water for at least 15 minutes. If irritation persists, seek immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. Clean affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

**SECTION 4 HEALTH HAZARDS & ROUTES OF ENTRY**

EYE CONTACT: This product may cause irritation.

SKIN CONTACT: This product may cause skin irritation. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

COMMENTS: THIS SUBSTANCE HAS NOT BEEN IDENTIFIED AS A CARCINOGEN OF PROBABLE CARCINOGEN BY NTP, IARC, OR OSHA.

**SECTION 5 SPECIAL PROTECTION INFORMATION**

VENTILATION: None required.

RESPIRATORY INFORMATION: No protection required

PROTECTIVE GLOVES: Rubber recommended.

EYE PROTECTION: Goggles.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in the work area for flushing eyes and skin. Protective clothing should be worn as needed.

**SECTION 6 REACTIVITY DATA**

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of nitrogen and carbon.

**SECTION 7 SPILL OR LEAK PROCEDURES**

PRECAUTION IN CASE OF LEAK OR SPILL: Mop up as much as possible, then flush residue with a large volume of water.

WASTE DISPOSAL METHOD: Dispose of product in accordance with applicable local, county, state and federal regulations.

**SECTION 8 STORAGE, SHIPPING, & REGULATORY INFORMATION**

HANDLING & STORAGE: Keep containers tightly closed. Keep containers cool and dry.

DOT PROPER SHIPPING NAME: Combustible liquid n.o.s.

DOT HAZARD CLASS: Combustible

HAZARD RATINGS	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	1	1
REACTIVITY	0	0

**SECTION 9 FIRE AND EXPLOSION HAZARD**

FLASH POINT (TEST METHOD): 145°F ASTM D93. AUTO IGNITION TEMPERATURE: N/A

FLAMMABLE LIMITS IN AIR. % BY VOL. LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: Use foam CO<sub>2</sub> or dry chemical fire fighting apparatus.

FIRE AND EXPLOSION HAZARD: Not determined.

FIRE FIGHTING PROCEDURES: The use of a self-contained breathing apparatus is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARD: N/A

**SECTION 10 PHYSICAL DATA**

BOILING POINT (°F): >212° F. SPECIFIC GRAVITY (H<sub>2</sub>O=1): ~1.0

VAPOR PRESSURE: Not known. MELTING POINT: N/A

SOLUBILITY IN WATER: Complete. VAPOR DENSITY: Not known.

APPEARANCE & ODOR: Tan viscous liquid-sweet odor. EVAPORATION RATE: Slower than ether.

**SECTION 11 DOCUMENTARY INFORMATION**

**DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES** The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.