

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

SPECIALTY ADHESIVE & COATINGS REMOVER

F O R M U L A

207

FAST-ACTING
REMOVES CURED GLUES

PRODUCT DESCRIPTION:

SENTINEL 207 SPECIALTY ADHESIVE REMOVER is a low-odor, fast-acting adhesive remover, specifically formulated to remove **urethanes, epoxies and PVA** adhesives and coatings.

DIRECTIONS:

(Always follow product label instructions for best results and test a small area first.)

To remove fresh, unhardened adhesive: Apply directly to the unwanted adhesive using a Sentinel microfiber towel. Rub and wipe frequently, turning the cloth as you wipe. Wipe until spot is dry, removing all adhesive residue. Use a clean towel as needed.

To remove dried adhesive: *(Small glue spots, fingerprints or haze on new flooring surfaces.)*

Saturate microfiber towel with product and wipe onto dried glue stain. Let product sit until glue softens. Wipe residue away with a clean towel or use a plastic putty knife if scraping is necessary to remove adhesive. Reapply more Sentinel 207 as needed to remove all adhesive.

Use Sentinel 810 to rinse and wipe cleaned area to remove any remaining remover and adhesive residue.

For removing flooring adhesives and coatings: *(Larger jobs or as a flooring adhesive remover.)*

Wet the entire surface with Sentinel 207. Allow product to penetrate and soak into adhesive. Thicker adhesive may take up to 60 minutes. Scrape the bulk of the softened adhesive from the floor using floor scrapers. If necessary, protect adjacent surfaces with an absorbent. Reapply 207 and agitate into any remaining adhesive using brooms or stripper pads. Absorb liquified adhesive with an absorbent. Wash and rinse floors thoroughly with Sentinel 810 and water to ensure a clean surface. Allow to dry completely. Dispose of spent remover and adhesive in accordance with local, county, state, and federal regulations.

For additional information or assistance with this product, please call Sentinel Customer Service at, **800-373-0633**.



SPECIFICATIONS:

APPEARANCE	Clear Viscous Liquid
APPROXIMATE BOILING POINT	>200°F
ODOR	SHARP
SPECIFIC GRAVITY	1.02
FLASHPOINT	>200°F TCC

See reverse side for
Material Safety Data Sheet (MSDS)

800-373-0633
www.senpro.com

Sentinel Products, Inc
51 NE 77th Ave
Minneapolis MN 55432

MATERIAL SAFETY DATA SHEET

Sentinel Products Inc. - 51 Northeast 77th Avenue, Minneapolis, MN 55432
PHONE (612)571-1399 - FAX(763)571-1819

Section 1 - Chemical Product and Company Identification

Product Trade Name SENTINEL 207 Specialty Adhesive Remover
Manufacturer Information Sentinel Chemical Co
51 NE 77TH AVE
Minneapolis, MN 55432

EMERGENCY/MEDICAL PHONE # 1-866-359-5661

Section 2 - Composition / Information on Ingredients

CAS # Component 100-51-6 Benzyl alcohol

Section 3 - Hazards Identification

Emergency Overview:

WARNING!

May be harmful if swallowed. Causes severe skin and eye irritation.

Causes respiratory tract irritation. May cause central nervous system effects.

Section 4 - First Aid Measures

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact: Immediately wash with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Ingestion: DO NOT induce vomiting unless directed by medical personnel. Get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Section 5 - Fire Fighting Measures

Flash Point: >200° F TCC

Upper Flammable Limit (UFL): NE

Lower Flammable Limit (LFL): NE

Fire & Explosion Hazards: None

Extinguishing Media: Use water fog, dry chemical or foam

Fire-Fighting Instructions: None.

Section 6 - Accidental Release Measures

Spill or Leak: Contain spill. Stop leak at source if this can be done safely. Ventilate area. Pump liquid into DOT-approved drums for disposal. Absorb remaining liquid onto inert absorbent and place in DOT approved drums for disposal. Wash area with water. Keep concentrate and wash water from entering sewers or waterways.

Section 7 - Handling and Storage

Storage Procedures: Store in a cool, dry place. Avoid excessive heat. Store out of direct sunlight in a cool, well ventilated place.

Section 8 - Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face Protective Equipment: Wear chemical goggles and have eye flushing equipment immediately available.

Skin Protection: Natural rubber or Neoprene gloves. Rinse contaminated skin promptly. Wash skin thoroughly after handling.

Respiratory Protection: Avoid breathing vapor or mists, use NIOSH approved respiratory protection.

Section 9 - Physical & Chemical Properties

Appearance: Clear viscous liquid

Odor: Sharp

Vapor Pressure: < 0.1 mmHg @ 20 C

Vapor Density: >1

Boiling Point: > 200 F

Specific Gravity: 1.02

Solubility Water: Moderate

Section 10 - Chemical Stability & Reactivity Information

Chemical Stability: Stable

Incompatibility: Avoid contact with strong acids and oxidizers.

Decomposition Products: Oxides of carbon.

Hazardous Polymerization: Hazardous polymerization is not known to occur.

DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.

Hazard Rating:	HMIS
HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL- PROTECTION	B