



# Another Sentinel Installation Innovation!

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

# ADHESIVE, SEAM & SPOT CLEANER

F O R M U L A

# 222

V.O.C.-COMPLIANT  
FAST-ACTING  
QUICKLY EVAPORATES

## PRODUCT DESCRIPTION:

**SENTINEL 222 Adhesive, Seam & Spot Cleaner is a fast-acting, high-strength remover, specially formulated to remove adhesive spots and grease from carpets, vinyl, and wood flooring. Works great as a seam cleaner for carpet and vinyl floor seams and for cleaning and degreasing metals.**

## DIRECTIONS:

*(Always follow product label instructions for best results and test a small area first.)*

### To remove small glue spots and stains on carpet or wood floors:

Apply Sentinel 222 to clean towel, rag or microfiber towel and wipe onto glue stain, haze or fingerprints. If glue has dried, allow 222 to penetrate and soften glue. Wipe spot until glue is gone, removing all adhesive residue. Turn cloth frequently, using a clean area each time to wipe the stain or spot. Allow floor to dry completely before walking on.

### To clean vinyl floor seams:

Apply 222 to microfiber towel or clean rag and wipe seam clean. 222 dries quickly so seam will be ready for sealing once dry.

### To remove carpet seam glue:

Simply wipe seam with 222 on a clean rag or cloth to remove residue. Allow area to dry.

For additional information or assistance with this product, please call Sentinel Customer Service at, **800-373-0633**.



## SPECIFICATIONS:

APPEARANCE	CLEAR
ODOR	clean scent
SPECIFIC GRAVITY	1.08
FLASHPOINT	109°F PMCC**
% VOC CONTENT	0 g/L*

See reverse side for  
Material Safety Data Sheet (MSDS)

\*When determining VOC content in accordance with the requirements set forth by the California Air Resource Board (CARB), effective 01-01-2008.  
\*\* This product is non-regulated under DOT Hazardous Materials Regulations and IMDG Code because it does not sustain combustion.

800-373-0633  
www.senpro.com

Sentinel Products, Inc  
51 NE 77th Ave  
Minneapolis MN 55432



**MATERIAL SAFETY DATA SHEET**Sentinel Products, Inc. – 51 N.E. 77<sup>th</sup> Avenue, Fridley, MN 55432 (763)571-0630 - FAX(763)571-1819**SECTION 1 PRODUCT IDENTIFICATION AND EMERGENCY INFORMATION**

PRODUCT NAME: SENTINEL 222 Adhesive, Seam and Spot Cleaner

EMERGENCY MEDICAL AND SPILL NUMBER: 1-866-359-5661

**SECTION 2 COMPONENT & EXPOSURE DATA**

COMPONENT	CAS#	PEL
PARACHLOROBENZOTRIFLUORIDE	98-56-6	2.5 mg/m <sup>3</sup>

**SECTION 3 EMERGENCY AND FIRST AID PROCEDURES**

EYE CONTACT: If this product comes in contact with eyes, gently flush with large quantities of water for at least 15 minutes. If irritation persists, seek immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

INHALATION: If breathing difficulties, dizziness, or light-headedness occur when working in areas with high vapor concentration, victim should seek air free of vapors. If breathing stops, begin artificial respiration and seek immediate medical attention.

INGESTION (SWALLOWING): If this product is swallowed, DO NOT induce vomiting unless directed by a physician. Seek immediate medical advice and/or attention.

**SECTION 4 HEALTH HAZARDS & ROUTES OF ENTRY**

EYE CONTACT: This product may cause irritation.

SKIN CONTACT: This product may cause skin irritation. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

INHALATION: Inhalation of excessive concentration of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue). Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties due to the irritant properties of the material.

INGESTION: Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue). Acute exposure to these compounds results in narcosis, pulmonary edema, and severe kidney and liver damage.

ASPIRATION HAZARD: This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

COMMENTS: THIS SUBSTANCE HAS NOT BEEN IDENTIFIED AS A CARCINOGEN OR PROBABLE CARCINOGEN BY NTP, IARC, OR OSHA.

**SECTION 5 SPECIAL PROTECTION INFORMATION**

VENTILATION: Local exhaust.

RESPIRATORY INFORMATION: Respiratory protection may be necessary to minimize exposure to organic vapors or gases. Depending on the nature and concentration of the airborne material, use a respirator or gas mask with appropriate cartridges and canisters, (NIOSH approved) or supplied air equipment.

PROTECTIVE GLOVES: Wear resistant gloves, such as nitrile or neoprene.

EYE PROTECTION: Approved eye protection is recommended to safeguard against eye contact, irritation or injury.

OTHER PROTECTIVE EQUIPMENT: It suggested that a source of clean water be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

**SECTION 6 REACTIVITY DATA**

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur

INCOMPATIBILITY (MATERIALS TO AVOID): Incompatible with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, fluorine, and chlorine.

**SECTION 7 SPILL OR LEAK PROCEDURES**

PRECAUTION IN CASE OF LEAK OR SPILL: Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. If spill is indoors, ventilate area of spill. Foam, especially high expansion foam, may be used to suppress vapors. Keep contained and dispose of in accordance with local, county, state, and federal regulations.

**SECTION 8 STORAGE, SHIPPING, & REGULATORY INFORMATION**

HANDLING &amp; STORAGE: Keep containers tightly closed. Keep containers cool, dry, and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks or other sources if ignition. "Empty" drums should be completely drained, properly bunged and promptly shipped to a qualified drum reconditioner.

DOT SHIPPING NAME: Cleaning compound, Class 55 NOS DOT HAZARD CLASS: NOT A REGULATED MATERIAL

HAZARD RATINGS	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	2	2
REACTIVITY	1	1

**SECTION 9 FIRE AND EXPLOSION HAZARD**

FLASH POINT (TEST METHOD): 109° F. TCC FLAMMABLE LIMITS IN AIR. % BY VOL. LOWER: 0.9 UPPER: 10.5

GENERAL HAZARDS: Product exhibits a flash point of 109°F, however, this product is a non-regulated material under DOT Hazardous Materials Regulations And IMDG Code because it does not sustain combustion.

EXTINGUISHING MEDIA: Small fires-Extinguish with dry chemical, CO<sub>2</sub> or foam. Large fires-The use of dry chemical or foam is recommended.

FIRE AND EXPLOSION HAZARD: Not determined. FIRE FIGHTING PROCEDURES: The use of a SCBA is recommended for fire fighters. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.

**SECTION 10 PHYSICAL DATA**BOILING POINT (°F): 282° F. SPECIFIC GRAVITY (H<sub>2</sub>O=1): 1.34 VAPOR DENSITY: Heavier than air.

APPEARANCE &amp; ODOR: Clear liquid-Strong solvent. VAPOR PRESSURE: 5.3mm/hg@68 F % VOLATILE: 0g/L\*

\*When determining VOC content in accordance with the requirements set forth by the California Air Resource Board (CARB), effective 01-01-2008.

**SECTION 11 DOCUMENTARY INFORMATION**

DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.