

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

CARPET & SHEET VINYL **ADHESIVE REMOVER**

FORMULA

626

BIODEGRADABLE
ODORLESS
NON-FLAMMABLE
WATER-BASED

PRODUCT DESCRIPTION:

SENTINEL 626 CARPET & SHEET VINYL ADHESIVE REMOVER is a powerful, biodegradable, formulation designed specifically for quickly removing latex, acrylic, and pressure-sensitive adhesives from concrete, terrazzo, ceramic, and vinyl tile or wood substrates.

DIRECTIONS: *(Always follow product label instructions for best results.)*

REMOVAL OF LATEX, ACRYLIC, & PRESSURE-SENSITIVE ADHESIVES

Step 1. Apply 626 directly onto adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the surface wet. Allow 626 to soak and penetrate for 30-60 minutes.

Step 2. Scrape softened adhesive from the floor (razor scrapers or squeegees are preferred). Repeat **Steps 1 and 2** if necessary. Dispose of all waste.

Step 3. Rinse the sub-floor thoroughly with clean water. Allow surface to completely dry.

REMOVAL OF SHEET VINYL/LINOLEUM BACKING: Once the wear layer is removed, mix 1 part HOT water to 4 parts 626 (1 quart of HOT water to 1 gallon of 626) and apply directly to the remaining backing. Maintain even coverage and a wet surface for 1-2 hours or until backing/adhesive can be easily removed together with a floor scraper. Rinse the surface with clean water and allow to dry.

REMOVAL OF CARPETING: Using a utility knife, cut the carpeting into 12" strips, making sure to cut through the carpeting to the sub-floor). Mix 2 parts HOT water to 1 part 626 (2 gallons HOT water to 1 gallon 626) and pour directly onto carpet. Maintain even coverage and completely saturate carpeting. Allow to soak for 4 hours, or overnight. Remove carpet strips and follow latex removal procedures for removing remaining adhesive.



For additional information or assistance with this product, please call Sentinel Customer Service at, **800-373-0633**.

SPECIFICATIONS:

APPEARANCE	CLEAR
APPROXIMATE BOILING POINT	212°F
ODOR	NONE
SPECIFIC GRAVITY (60°F)	>1
FLASHPOINT	NONE
%VOC	not greater than 35g/L*

See reverse side for
Material Safety Data Sheet (MSDS)

*When determining VOC concentrations in accordance with the requirements set forth by the California Air Resource Board (CARB) and the Ozone Transport Commission (OTC), effective 01-01-2009.

MATERIAL SAFETY DATA SHEET

Sentinel Products Inc. - 51 Northeast 77th Avenue, Minneapolis, MN 55432 - (763)571-0630 - (FAX)763-571-1819

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: SENTINEL® 626 CARPET ADHESIVE REMOVER

SYNONYMS: DETERGENT

EMERGENCY MEDICAL NUMBER: 1-866-359-5661

SECTION 2 COMPONENT & EXPOSURE DATA

COMPONENT	CAS#	TLV
Monoethanolamine	141-43-5	3 ppm (OSHA & ACGIH)

SECTION 3 EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush with water for 15 minutes while holding eyelids open. Get medical attention promptly.

SKIN CONTACT: Flush with water while removing contaminated clothing and shoes. Follow by washing with soap and water. Do not reuse clothing and shoes until cleaned. If irritation persists, get medical attention as soon as possible.

INHALATION: Move to fresh air. Seek medical attention if symptoms are present.

INGESTION (SWALLOWING): If swallowed do not induce vomiting. Never give anything by mouth to a drowsy or unconscious person. Give large quantities of water (preferably several glasses of milk, if available). Get medical attention as soon as possible.

SECTION 4 HEALTH HAZARDS & ROUTES OF ENTRY

EYE CONTACT: Irritating to the eyes, may cause burns and possible corneal damage.

SKIN CONTACT: May be irritating to the skin.

INHALATION: Breathing spray or mists may be irritating the respiratory tract.

INGESTION (SWALLOWING): May be irritating to the mucous membranes.

COMMENTS: THIS PRODUCT HAS NOT BEEN IDENTIFIED AS A CARCINOGEN OR PROBABLE CARCINOGEN BY NTP, IARC, OR OSHA.

SECTION 5 SPECIAL PROTECTION INFORMATION

VENTILATION: Use adequate local exhaust ventilation where mist, dust or spray may be generated.

RESPIRATORY INFORMATION: Use in a well ventilated area.

PROTECTIVE GLOVES: Rubber.

EYE PROTECTION: Wear protective eye ware.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in the work area for flushing eyes and skin.

SECTION 6 REACTIVITY DATA

STABILITY: Stable **HAZARDOUS POLYMERIZATION:** Will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with acids or bleach.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon and Nitrogen.

SECTION 7 SPILL OR LEAK PROCEDURES

PRECAUTION IN CASE OF LEAK OR SPILL: CAUTION! SPILL AREA WILL BE SLIPPERY! Mop up as much as possible, then flush residue with a large volume of water.

WASTE DISPOSAL METHOD: Dispose of product in accordance with applicable local, county, state and federal regulations.

SECTION 8 STORAGE, SHIPPING, & REGULATORY INFORMATION

HANDLING & STORAGE: Keep containers tightly closed. Keep containers cool and dry.

DOT PROPER SHIPPING NAME: Not regulated

DOT HAZARD CLASS: Not a regulated material. **FREIGHT CLASSIFICATION:** Compound Cleaning, NOIBN

HAZARD RATINGS	HMS	NFPA
HEALTH	1	1
FLAMMABILITY	0	0
REACTIVITY	0	0

SECTION 9 FIRE AND EXPLOSION HAZARD

FLASH POINT (TEST METHOD): None to boiling.

AUTO IGNITION TEMPERATURE: N/A

FLAMMABLE LIMITS IN AIR, % BY VOL.

LOWER: N/A

UPPER: N/A

EXTINGUISHING MEDIA: Use foam, CO₂ or dry chemical fire fighting apparatus.

FIRE AND EXPLOSION HAZARD: None

SECTION 10 PHYSICAL DATA

BOILING POINT (°F): >212° F.

SPECIFIC GRAVITY (H₂O=1): ~1.008

VAPOR PRESSURE: Not known.

MELTING POINT: N/A

SOLUBILITY IN WATER: Complete

VAPOR DENSITY: Not known

APPEARANCE & ODOR: Clear/No odor

EVAPORATION RATE: Slower than ether.

***VOC Content:** not greater than 35g/L.

*When determining VOC content in accordance with the requirements set forth by the California Air Resource Board (CARB) and The Ozone Transport Commission (OTC), effective 01-01-2009.

SECTION 11 DOCUMENTARY INFORMATION

DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.