

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

MULTI-SURFACE ADHESIVE PRIMER

F O R M U L A

811

HIGH PERFORMANCE
LOW ODOR
FAST DRYING
IMPROVES BONDING ABILITY
OF ADHESIVES

PRODUCT DESCRIPTION:

SENTINEL 811 ADHESIVE PRIMER is a low odor, high performance primer, designed to increase the adhesion of floor and wallpaper adhesives. Use prior to installing peel & stick tile, sheet vinyl, carpet, carpet tile, wallpaper, and paneling on most surfaces, including portland and gypsum-based building materials.

DIRECTIONS: *(Always follow product label instructions for best results.)*

Use Sentinel 811 only in areas where the temperature is above 50° F.

- Step 1.** All surfaces must be clean and completely dry before application. Clean surfaces with Sentinel 810 All-Surface Floor Cleaner before applying 811.
- Step 2.** Shake or stir contents of 811 prior to use. Product must NOT be reduced with water or solvents. 811 will appear somewhat milky when first applied but will dry clear.
- Step 3.** 811 may be applied using a brush, roller or sprayer. Apply in a thin, uniform coat. Do not overapply. Coverage of product will range from 200-400 ft²/gallon. Allow first coat to dry completely (30-60 minutes in ideal drying conditions). Depending upon the porosity of the substrate being primed, a second coat may be desired for optimal results.
- Step 4.** Apply second coat as needed and allow to dry. Second coat will take longer to dry than the first coat, so allow ample time for product to dry completely.

For additional information or assistance with this product, please call Sentinel Customer Service at **800-373-0633**.



Note: Not intended for exterior use or as a general paint primer. Allow to dry completely before applying products over 811. Dry times will vary based upon environmental conditions and substrate being primed. Allow more dry time when applying 811 to finished surfaces or in areas of higher humidity.
Clean-up: Equipment may be cleaned with soap and water, while 811 is still wet.

See reverse side for Material Safety Data Sheet (MSDS)

800-373-0633
www.senpro.com

Sentinel Products, Inc
51 NE 77th Ave
Minneapolis MN 55432

MATERIAL SAFETY DATA SHEET

Sentinel Products Inc. - 51 Northeast 77th Avenue, Minneapolis, MN 55432 - (763) 571-0630 – FAX (763) 571-1819

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: Sentinel 811 All-Surface Floor Primer

SYNONYMS: EMULSIFIED POLYMER

EMERGENCY MEDICAL AND SPILL NUMBER: 1-866-359-5661

SECTION 2 COMPONENT & EXPOSURE DATA

COMPONENT	%	CAS#
-----------	---	------

SECTION 3 EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: If this product comes in contact with eyes, gently flush with water for at least 15 minutes. If irritation persists, seek immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

IF SWALLOWED: Drink a glass of water. Contact medical assistance.

SECTION 4 HEALTH HAZARDS & ROUTES OF ENTRY

EYE CONTACT: This product may cause irritation.

SKIN CONTACT: This product may cause mild skin irritation.

IF SWALLOWED: Gastric discomfort.

COMMENTS: THIS SUBSTANCE HAS **NOT** BEEN IDENTIFIED AS A CARCINOGEN OF PROBABLE CARCINOGEN BY NTP, IARC, OR OSHA.

SECTION 5 SPECIAL PROTECTION INFORMATION

VENTILATION: None required.

RESPIRATORY INFORMATION: No protection required

PROTECTIVE GLOVES: None required.

EYE PROTECTION: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

OTHER PROTECTIVE EQUIPMENT: None

SECTION 6 REACTIVITY DATA

STABILITY: Stable **HAZARDOUS POLYMERIZATION:** Will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon and Nitrogen.

SECTION 7 SPILL OR LEAK PROCEDURES

PRECAUTION IN CASE OF LEAK OR SPILL: Mop up as much as possible, then flush residue with a large volume of water.

WASTE DISPOSAL METHOD: Dispose of product in accordance with applicable local, county, state and federal regulations.

SECTION 8 STORAGE, SHIPPING, & REGULATORY INFORMATION

HANDLING & STORAGE: Keep containers tightly closed. Keep containers cool and dry.

DOT PROPER SHIPPING NAME: Not regulated

DOT HAZARD CLASS: Not a regulated material.

HAZARD RATINGS

	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	0	0
REACTIVITY	0	0

SECTION 9 FIRE AND EXPLOSION HAZARD

FLASH POINT (TEST METHOD): None to boiling. **AUTO IGNITION TEMPERATURE:** N/A

FLAMMABLE LIMITS IN AIR. % BY VOL. **LOWER:** N/A **UPPER:** N/A

EXTINGUISHING MEDIA: Use foam CO₂ or dry chemical fire fighting apparatus.

FIRE AND EXPLOSION HAZARD: None.

FIRE FIGHTING PROCEDURES: The use of a self-contained breathing apparatus is recommended for fire fighters.

UNUSUAL FIRE AND EXPLOSION HAZARD: N/A

SECTION 10 PHYSICAL DATA

BOILING POINT (°F): 212° F. **SPECIFIC GRAVITY (H₂O=1):** 1.014

VAPOR PRESSURE: Not known. **MELTING POINT:** N/A

SOLUBILITY IN WATER: Complete. **VAPOR DENSITY:** Not known.

APPEARANCE & ODOR: White liquid-no odor. **EVAPORATION RATE:** Slower than ether.

SECTION 11 DOCUMENTARY INFORMATION

DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.