



HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

# Flooring ADHESIVE REMOVER WIPES

FORMULA

# 922

## PRODUCT DESCRIPTION:

SENTINEL 922 ADHESIVE REMOVER WIPES are formulated to remove all flooring adhesives, including wet, and cured urethane adhesives from most pre-finished (not-waxed) flooring surfaces and tools.

EASY-TO-USE WIPES  
PRE-SOAKED TOWELS  
REMOVES URETHANES  
POWERFUL ORGANIC FORMULA

## DIRECTIONS: (Always follow product label instructions for best results.)

For use as a urethane release agent:

Wipe finished surface (top) of each board with Sentinel 922 wipes prior to spreading urethane glues to ensure easy clean-up of urethane adhesives on finished wood floors. Be sure to thoroughly wash the newly installed floor with Sentinel 810 All-Surface Floor Cleaner once installation is complete to remove remaining 922. **CAUTION:** Floor will be extremely slippery with remover residue on the wood surface.



See reverse side for  
Material Safety Data Sheet (MSDS)

For general adhesive removal:

1. Unscrew container lid, remove and discard foam seal. Pull up corner of towel from center of roll, twist to a point and thread through the hole in the underside of the lid. Replace lid and make sure it is tight. Pull up towel and tear at perforation. Close snap-down lid to keep towels from drying out when not in use.
2. Rub area of floor that has cured or wet adhesive with 922 towel.
3. If adhesive has cured for more than 48 hours, lay a 922 towel over the cured adhesive and let stand for about 5 minutes. Wipe area clean with a fresh towel.
4. Once adhesive has been removed, wipe entire area with a clean, water-dampened cloth to remove any remaining remover.

**NOTE:** Be sure NOT to scrub the surface of the finished wood too aggressively as this will change the look of the finish. Do NOT allow excess remover to drip between floor boards. Close cap when not in use. Store in a clean, dry area.

For additional information or assistance with this product, please call Sentinel Customer Service at, **800-373-0633**.

800-373-0633  
www.senpro.com

Sentinel Products, Inc  
51 NE 77th Ave  
Minneapolis MN 55432

**MATERIAL SAFETY DATA SHEET**

Sentinel Products, Inc. – 51 NE 77<sup>th</sup> Ave, Minneapolis, MN 55432  
(763)571-0630 - FAX (763)571-1819

**SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION**

PRODUCT NAME: SENTINEL 922 URETHANE ADHESIVE REMOVER

CHEMICAL: Not Applicable, mixture SYNONYMS: None

EMERGENCY MEDICAL AND SPILL NUMBER 1-866-359-5661

**SECTION 2 COMPONENT & EXPOSURE DATA**

COMPONENT	CAS#	PEL	TLV	%
DIMETHYL GLUTERATE	1119-40-0	28-35		
DIMETHYL ADIPATE	627-93-0	9-18		

**SECTION 3 HEALTH INFORMATION**

EFFECTS OF OVEREXPOSURE: May cause eye and respiratory tract irritation-May cause blurred vision

EYE CONTACT: This material may cause pain, redness, and tearing based on toxicity studies. May cause blurred vision.

SKIN CONTACT: This material may cause skin irritation. Prolonged or repeated exposure may cause redness, burning, drying or cracking of skin or dermatitis.

INHALATION: This product may cause upper respiratory irritation.

INGESTION (SWALLOWING): LD50>50ml/kg (albino rats)(similar products)

**SECTION 4 OCCUPATIONAL EXPOSURE LIMITS**

PEL: NO OSHA PEL TLV: NO ACGIH TLV

**SECTION 5 EMERGENCY FIRST AID PROCEDURES**

FOLLOW STANDARD FIRST AID PROCEDURES:

SWALLOWING: Call physician or poison control center.

SKIN CONTACT: Wash affected area.

EYE CONTACT: Flush eyes with cool water for at least 15 minutes. Do not let victim rub eyes.

INHALATION: Immediately remove victim to fresh air. Get medical attention immediately.

**SECTION 6 PHYSICAL DATA**

BOILING POINT: Over 400 degrees F (204 degrees C) at 760 mm Hg pressure

VAPOR PRESSURE: Less than .2 mm Hg at 68 degrees F

SPECIFIC GRAVITY: 0.97 AT 25 degrees c

SOLUBILITY IN WATER: Negligible at room temperature

APPEARANCE AND COLOR: Light yellow to amber and liquid at room temperature

ODOR: Light musty odor

**SECTION 7 FIRE AND EXPLOSION HAZARDS**

FLASH POINT & METHOD USED: >200 °F (PMCC)

FLAMMABLE LIMITS: Not applicable NFPA RATING: No NFPA rating

HMIS RATING: HEALTH: 1 FIRE: 1 REACTIVITY: 0

SPECIAL FIRE FIGHTING PROCEDURES & PRECAUTIONS: Treat as oil fire. Use water spray, dry chemical, foam or carbon dioxide.

USUAL FIRE & EXPLOSION HAZARDS: Rags soaked with any solvent present a fire hazard and should always be stores in UL listed of Factory Mutual approved, covered containers. Improperly stored rags can create conditions that lead to oxidation. Oxidation, under certain conditions can lead to spontaneous combustion. This product contains antioxidants to retard oxidation.

**SECTION 8 REACTIVITY**

STABILITY: Stable HAZARDOUS POLYMERIZATION: None Likely

MATERIAL TO AVOID: Strong oxidizing agents HAZARDOUS DECOMPOSITION PRODUCTS: CO2, CO

CONDITIONS TO AVOID: Strong oxidants, acids and alkalis

**SECTION 9 EMPLOYEE PROTECTION**

CONTROL MEASURES; Adequate Ventilation

RESPIRATORY PROTECTION: Avoid breathing vapor or mist. Use NIOSH/MSHA approved respiratory protection equipment.

PROTECTIVE CLOTHING: No need anticipated

EYE PROTECTION: Wear chemical goggles and have eye flushing equipment available.

**SECTION 10 ENVIRONMENTAL PROTECTION**

ENVIRONMENTAL PRECAUTIONS: Avoid uncontrolled releases of this material to environment.

SPILL OR LEAK PRECAUTIONS: Contain spilled material. Transfer to secure containers. Where necessary, collect using absorbent media.

WASTE DISPOSAL: Dispose of according to federal, state and/or local requirements.

**SECTION 11 REGULATORY CONTROLS**

DOT CLASSIFICATION: CLASS 55

DOT PROPER SHIPPING NAME: Cleaning Compound

OTHER REGULATORY REQUIREMENTS: Listed in TSCA inventory

**SECTION 12 DOCUMENTARY INFORMATION**

DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.