



SenPro How-To Series

Topic: Mastic and Indoor/Outdoor Adhesive Removal Tips & Tricks

Use

FORMULA
747

BIODEGRADABLE
FRESH SCENT
FAST-ACTING
GREATER COVERAGE RATES

Or

FORMULA
747 PLUS

BIODEGRADABLE
LOW ODOR FORMULA
FASTER ACTING
GREAT COVERAGE RATES
(100-200 FT²/GALLON)

- For best results, use our products at room temperature, read all instructions before using and test in a small area first.
- When used in accordance with the directions for use, our products will safely remove most mastics and solvent-based flooring adhesives, leaving a clean surface that is ready for recoating, staining, or new adhesives.
- Refer to the installation instructions for any new product being applied after using our products to determine necessary dry times and other surface preparation requirements. As always, feel free to contact Sentinel with any additional questions that you may have.

For best results, use the information below in combination with the directions for use on the product label or the technical data sheet.

- Let's face it, people may not always use glues or adhesives that are appropriate for a particular application, so contact us if you have questions about the type of glue you are removing. Chances are, we've seen it before and make a product that will remove it.
- Typically, most mastics and solvent-based glues are hard to the touch and black or green in color. If you have a tan, beige, or yellow glue, try our 626 product.
- Most issues with a product not working, **especially on indoor/outdoor carpet glue**, can be corrected by doing two things, allow the product to soak and penetrate for a longer period of time before scraping AND keep the glue saturated with product and DO NOT let it dry out.
- Limit the application of 747 to the adhesive only. The majority of complaints about odors remaining after adhesive removal are the result of 747 being dumped or splashed into adjacent materials like carpeting or baseboards, or left in cracks or drains and not being completely cleaned up. Odors will dissipate over time but can be avoided by proper application and thorough clean up.
- To remove all of the glue, the remover needs to penetrate down to the subfloor, so don't start removing too soon as you may only remove the portion of the glue that has been softened by the remover. **Give the product time to work.**
- Once adhesive removal is completed wash and rinse the subfloor with Sentinel 810 All-Surface Floor Cleaner, or a mixture of soap and warm water to remove any remaining 747 from the floor and allow the floor to dry completely.
- As with any chemical or liquid adhesive remover, 747 may get into cracks or spaces between wooden floor boards when used to remove adhesives from on top of existing hardwood floors. Thorough cleaning of the floor once all adhesive has been removed should remove the majority of the product.
- Free-standing liquids should not be disposed of. Solidify all removed glue and residue with an absorbent like saw-dust or kitty litter before throwing away.

As always, feel free to contact our technical support staff at 800-373-0633 with any questions that you might have.

Sentinel Products, Inc.
51 NE 77th Avenue
Minneapolis MN 55432
800-373-0633 or www.senpro.com



HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

Visit www.senpro.com to view technical data sheets and Material Safety Data Sheets for all of our products.