## **PRODUCT DATA SHEET**



# FORMULA 24-7 INTERIOR MOLD & MILDEW RESISTANT COATING

### **Product Description**

Sentinel 24-7 Interior is a high-quality coating designed for most interior apllications. Formulated with the same Microban<sup>®</sup> protection as our 24-7 Premium Coating, Sentinel 24-7 Interior offers contractors and home owners alike a durable coating that can be tinted to match decor. Ideal for high traffic interior areas, Sentinel 24-7 Interior is designed to inhibit the growth of stain and odor causing microorganisms such as mold and mildew on cured coating surfaces.

#### Application Information (Always follow product label instructions for best results)

#### **Material Preparation:**

Thoroughly stir and mix coating to achieve an even consistency for spraying, brushing or rolling. Product must NOT be reduced with water or solvents. This product must not be allowed to freeze. Apply in temperatures above 50° F.

#### Surface Preparation:

Wash and clean surfaces to remove mold, mildew, grease, dirt and other soils with a suitable cleaning compound like Sentinel 300. Rinse surface thoroughly with water and allow to dry before applying coating. Remove peeling paint, spackle and sand where necessary. Lightly sand all glossy areas. On new sanded sheetrock surfaces, remove all

new, sanded sheetrock surfaces, remove all dust before painting.

#### Tinting:

The white version of this product may be tinted with up to 4 oz. of colorant /per gallon.

#### Product Application:

All surfaces must be clean and completely dry before applying. To assure proper antimicrobial protection, it is vitally important that all surfaces be completely coated with 24-7 Interior Coating. For airless applications, use a .015 -.019 tip and maintain a fan size of about 12 inches. Coating applied at 90° to each other ensures a smooth and consistent application.

#### Primers:

On surfaces such as framing lumber, sheetrock and plaster, apply one coat of this product, it has self-priming properties built in. On new woodwork, use an oil-based primer then coat. On metal, use a suitable, rust inhibiting primer then coat.

#### Dry Time:

This product will be dry to the touch in 1 hour and may be recoated in 4 hours.

#### Coverage:

For smooth surfaces, apllied at 1 mil thickness, expect approximately 250 - 300 Sq. Ft. per gallon coverage.

#### Limitations:

This product does NOT protect users or others against foodborne or disease causing bacteria. This product is not designed to be used inareas with temperatures less than 50° F., excessive heat, corrosive chemical environments, or on exterior siding or horizontal floor and deck areas.

#### **Charactersistics**

Pounds Per Gallon: 9.83 Percent of Solids/weight: 41.11% Percent of Solids/Volume: 30.18% Viscosity,KU: 102 Specular Gloss @ 60° F. 22.4 Flash Point: : > 199.4° F. Shelf Life: Up to five years VOC Content: 129 Coverage on Smooth Surface Spread @ 1 mil: 485 Sq ft per/gl







PRODUCT DATA SHEET

# 24-7 INTERIOR MOLD & MILDEW RESISTANT COATING

## SENTINEL 24-7 INTERIOR MOLD & MILDEW RESISTANT COATING

Sentinel 24-7 Interior is a high-quality coating designed for most interior applications. Formulated with the same Microban<sup>®</sup> protection as our 24-7 Premium Coating, Sentinel 24-7 Interiors offers contractors and home owners alike a durable coating that can be tinted to match decor. Ideal for high traffic interior areas, Sentinel 24-7 Interior is designed to inhibit the growth of stain and odor causing microorganisms such as mold and mildew on cured coating surfaces.



## **Sentinel**

## AVAILABLE IN A WHITE OR CLEAR FINISH

**INTERIOR USE ONLY** 

# 800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445