

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

PeroxyStrip

PAINT & COATING STRIPPER

FORMULA

206

PEROXIDE
POWER

PRODUCT DESCRIPTION:

SENTINEL 206 PEROXYSTRIP PAINT & COATING STRIPPER is an environmentally safe stripper, powerful enough to dissolve most paint and coatings. PEROXYSTRIP is formulated with non-hazardous ingredients and is boosted with the power of hydrogen peroxide. PEROXYSTRIP's thick gel allows for easy use, especially on vertical surfaces and it rinses with water, making for fast clean-up. This low odor, nonflammable formula is safe for both interior & exterior projects.

DIRECTIONS: (Always follow product label instructions for best results.)

Before use, read all instructions. Shake well before use and product will pour easier. Cover all adjacent surfaces to protect them from incidental contact with 206.

1. Pour 206 onto the surface being stripped and spread with a rag or a paint brush. For best results, apply a generous amount of 206 to surface.
2. Let 206 penetrate the coating being removed. Times will vary based on thickness of coating. Varnish, shellac, and lacquer: 15-30 minutes. Latex/oil-based paints, polyurethane, and multi-layered finishes: 15 - 60+ minutes. For difficult to remove, multi-layered coatings, allow 206 to penetrate overnight.
3. Test scrape a small area of the surface with a putty knife to see if finish has softened. If not, let continue to soak.
4. Remove 206 and softened coating immediately after coating has softened by gently scraping with putty knife/ stripper tool. If removing multiple layers and surface remains grimy, a second application of 206 may be necessary.
5. Remove any remaining softened finish with a stripper pad dampened with soapy water. Always rub in the direction of the grain. Remove any leftover residue with a stripper pad dampened with water or mineral spirits.
6. Wipe surface with a dry, clean cloth. Let wood dry thoroughly (at least 24 hours) before refinishing.

REMOVAL OF LEAD-BASED PAINT: Only appropriately trained professionals should remove lead-based paint. Dispose of lead-based paint residue in accordance with federal, state, & local guidelines.

For additional information or assistance with this product, please call Sentinel Customer Service at, 800-373-0633.

