



FORMULA PL145
LOW ODOR MASTIC REMOVER
 LOW ODOR / ECONOMICAL / V.O.C. COMPLIANT

Product Description

Sentinel PL145 Low Odor Mastic Remover is a high strength, economically priced mastic remover designed for removing black mastic commonly found under 9" and 12" vinyl floor tile.

Application Information (Always follow product label instructions for best results)

DIRECTIONS:

Before beginning work, protect all walls, flooring, carpeting, cracks or wood with an absorbent from liquid materials. This will ensure easier clean-up and eliminate potential problems

STEP 1:

Wet the entire adhesive surface with PL145. This may be done by spraying or mopping PL145 over the surface of the mastic. Allow PL145 to soak and penetrate into the mastic for 20 - 30 minutes.

STEP 2:

Scrape or squeegee the bulk of the softened or liquefied mastic from the surface with a floor scraper (razor scraper) or floor squeegee.

STEP 3:

Reapply PL145 as in step one. Agitate with a short-bristled broom, hand-held or rotating floor scrubber with stripper pads to fully lift and liquefy adhesive residue from the subfloor. The liquid may then be removed with absorbent.

STEP 4:

Wash and rinse the floor thoroughly with Sentinel 805 and water to ensure a clean surface. Allow to dry a minimum of 24 hours before installing new flooring.

COVERAGE:

Expect coverage rates of 100-200 sq. feet per gallon.

V.O.C. CONTENT:

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

WARRANTY NOTICE:

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

HAZARD RATING: HMIS
 HEALTH 1
 FLAMMABILITY 2
 REACTIVITY 0
 PERSONAL PROTECTION H

PROPERTIES

Physical state: Liquid

Appearance: Clear

Color: None to amber

Odor: Mild Solvent Odor

pH: Not Applicable

Boiling Point: 363-381° F.

Flash Point: 170° F.

Vapor Pressure: <0.5 mm Hg@68° F.

VOC Content: <45g/l*

* When determining VOC content in accordance with the requirements set forth by the Ozone Transport Commission (OTC), effective 01-01-2009



PL145 LOW ODOR MASTIC REMOVER

V.O.C. COMPLIANT

SENTINEL PL145 LOW ODOR MASTIC REMOVER

Sentinel PL145 Low Odor Mastic Remover is a high strength, economically priced mastic remover designed for removing black mastic commonly found under 9" and 12" vinyl floor tile.



Low Odor / Economical / Greater Coverage Rates

800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445