

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

626

LOW ODOR  
NON FLAMMABLE  
NON HAZARDOUS SOLVENT



\*This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, effective 1-1-2009.



CARPET & ADHESIVE  
SHEET VINYL

REMOVER

PRODUCT DESCRIPTION

SENTINEL 626™ CARPET & SHEET VINYL ADHESIVE REMOVER is a powerful, biodegradable formulation designed specifically for quickly removing latex, acrylic and pressure sensitive adhesives from concrete, terrazo, ceramic and vinyl tile or wood substrates. For best results use at room temperature and read instructions before using.

USAGE GUIDELINES

**FOR BEST RESULTS:** Open container and fill remaining space in pail with HOT water before applying. Calculate coverage at 70 sq. ft. per gallon. **NOTE:** Coverage rates will vary based upon the thickness and quality of the adhesive being removed and room temperature.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling, and use, or effect of that use.



DANGER

(Contains: 2-aminoethanol, 2-(2-butoxyethoxy) ethanol, Alcohol Ethoxylate)

HAZARD STATEMENTS: Causes skin irritation. Causes serious eye damage.  
PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves.  
IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents /container to licensed waste handling facility.  
FIRST AID: EYES- IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). get medical advice/ attention.Skin- IF ON SKIN: immediately rinse with water (for at least 15 minutes). Get medical advice/attention. Inhalation- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. Ingestion- IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Obtain emergency medical attention.  
HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. REFER TO SDS FOR MORE INFORMATION

FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

FORMULA

626

LOW ODOR  
NON FLAMMABLE  
NON HAZARDOUS SOLVENT

FOR SPECIAL INSTRUCTIONS CONTACT  
SENTINEL'S CUSTOMER SERVICE AT 1.800.373.0633  
OR VISIT US AT www.senpro.com

HAZARD RATING: HMIS  
HEALTH 1  
FLAMMABILITY 1  
REACTIVITY 1  
PERSONAL PROTECTION H

DIRECTIONS

REMOVAL OF LATEX, ACRYLIC AND PRESSURE-SENSITIVE ADHESIVES

**STEP ONE:** Apply SENTINEL 626™ directly to the adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the adhesive surface wet. Allow SENTINEL 626™ to soak and penetrate for 45-90 minutes.

**STEP TWO:** Agitate with a stiff broom or stripper pads and scrape softened adhesive from the floor with a scraper (razor scrapers or squeegees are generally preferred). Repeat steps one and two if necessary and dispose of the waste.

**STEP THREE:** Rinse the sub-floor thoroughly with clean water. Allow surface to dry completely.

REMOVAL OF SHEET VINYL/LINOLEUM BACKING

Once the wear layer is removed, mix 1 part HOT water to 4 parts SENTINEL 626™ ( 1 gallon of HOT water to 1 gallon of 626™) and apply directly to remaining backing. Maintain even coverage and wet surface for 1-2 hours or until the backing and adhesive can be easily removed together. Agitate adhesive residue with stiff broom or stripper pads and remove with a floor scraper. Rinse the surface with clean water. Allow to dry.

REMOVAL OF CARPETING

Using a utility knife, cut the carpeting into 1-foot strips (making sure to cut through the carpeting to the sub-floor). Mix 1 part HOT water to 1 part SENTINEL 626™ (1 gallon HOT water to 1 gallon 626™) and pour directly onto carpet to be removed at a rate of 30 square feet per gallon. Maintain even coverage and completely saturate the carpet with SENTINEL 626™. Allow to soak for 4 hours or overnight. Pick up carpet strips and follow latex removal procedures above.



Sentinel Products Inc.  
Minneapolis, MN 55432  
800-373-0633  
www.senpro.com