

HIGH-PERFORMANCE



ECO-FRIENDLY PRODUCTS

FORMULA

717 GEL

A low-odor, viscous product designed for removing tile & carpet adhesives from vertical surfaces, and cracked or degraded subfloors.

THICKENED MASTIC REMOVER GEL



*V.O.C. Compliant

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

PRODUCT DESCRIPTION

Sentinel 717 THICKENED MASTIC REMOVER GEL is designed to remove most flooring adhesives and rinse leaving no residue. When subfloors are dry, new flooring may be confidently installed. Given it's thickened formula, 717 also works better at removing mastics from cracked, degraded, or vertical surfaces while reducing the chances of mastic and remover leaking through subfloors.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling, and use, or effect of that use.

HAZARD RATING: HMIS

HEALTH 1

FLAMMABILITY 2

REACTIVITY 0

PERSONAL PROTECTION H



DANGER

(Contains: Petroleum distillates, hydrotreated light, Solvent naphtha, petroleum, heavy aromatic, 2-(2-butoxyethoxy)ethanol, 2-aminoethanol Surfactant Blend, Fragrance)

HAZARD STATEMENTS: Combustible liquid. Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Do not breathe mists. Avoid breathing vapors/spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Remove/ take off immediately all contaminated clothing. Rinse skin with water. Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a comfortable position for breathing. Immediately call a POISON CENTER. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. Immediately call a POISON CENTER. IF SWALLOWED: Immediately call a POISON CENTER. Rinse mouth. Do NOT induce vomiting. Avoid release into the environment. In case of fire: Use a dry chemical, foam, CO2 for extinction. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container to licensed waste handling facility. FIRST AID: EYES- IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). Get medical advice/ attention. Skin- IF ON SKIN: immediately rinse with water (for at least 15 minutes). Get medical advice/attention. Inhalation- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. If breathing stops, begin artificial respiration and seek immediate medical attention. Ingestion- IF SWALLOWED: Rinse mouth, Do NOT induce vomiting. Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from: Heat sources. Keep container closed when not in use. REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

DIRECTIONS

ADHESIVE REMOVAL:

Note: 717 GEL is a pourable, thickened product, that can be made thicker with the addition of small amounts of water when being used on cracked, or degraded subfloors, and vertical surfaces.

STEP ONE: If necessary, protect walls, drains, and other flooring with plastic and absorbent (rags, kitty-litter or sawdust) to keep liquified adhesive contained.

STEP TWO: Apply 717 to surface of adhesive and allow to soak and penetrate the adhesive for 45-60 minutes.

STEP THREE: For heavier adhesives, scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scrapers are generally preferred). This will help increase the coverage of 717 and reduce the amount of liquid generated, and make final clean-up easier.

STEP FOUR: Reapply 717 and agitate with hand-held or rotating floor scrubber with stripper pads or short-bristled brooms to fully lift and liquefy adhesive residue from the subfloor. This liquid may then be removed with absorbent.

STEP FIVE: Wash and rinse the floor thoroughly with Sentinel Envirowash 805 or Sentinel 810 and water to ensure a clean surface. Allow surfaces to dry.



- LOW-ODOR
- THICKENED PRODUCT
- REMOVES TILE & CARPET ADHESIVES



Sentinel Products, Inc.
8901 Wyoming Ave. N
Brooklyn Park MN 55445
800-373-0633
www.senpro.com