

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

7200

NO ODOR/200° FLASH MASTIC REMOVER

**NO ODOR
FASTER ACTING
GREATER COVERAGE
OVER 200° FLASH**



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



PRODUCT DESCRIPTION

SENTINEL 7200 NO ODOR/200 FLASH MASTIC REMOVER is a high flash stripping solution designed to remove asphalt cutback adhesives and rinse leaving no residue. When subfloors are dry, new flooring may be confidently installed.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling, and use, or effect of that use.



DANGER

**(Contains: Petroleum distillates, hydrotreated light, 2-(2-butoxyethoxy)ethanol, Surfactant)
May be fatal if swallowed and enters airways.**

HAZARD STATEMENTS: May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. If swallowed, do NOT induce vomiting. IN CASE OF FIRE: Use dry chemical, foam, CO2 for extinction. STORAGE: Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID: Eyes – IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention. Skin – IF ON SKIN: Immediately rinse with plenty of soap and water (for at least 15 minutes). If skin irritation persists: Get medical advice/attention. Inhalation – IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. Ingestion – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking. Keep only in the original container in a cool, well ventilated place away from: Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION • FOR INDUSTRIAL USE ONLY • KEEP OUT OF REACH OF CHILDREN

FORMULA



**NO ODOR
FASTER ACTING
GREATER COVERAGE
OVER 200° FLASH**

HAZARD RATING: HMIS
HEALTH 1
FLAMMABILITY 1
REACTIVITY 0
PERSONAL PROTECTION H

FOR SPECIAL INSTRUCTIONS CONTACT
SENTINEL'S CUSTOMER SERVICE AT 1.800.373.0633
OR VISIT US AT www.senpro.com

DIRECTIONS

BLACK CUTBACK ADHESIVE REMOVAL
STEP ONE: Wet the entire adhesive surface with 7200. This may be done by using a garden sprayer or by mopping 7200 over the surface of the adhesive. DO NOT over apply 7200 in the first step. Allow 7200 to soak and penetrate for 10-20 minutes.
STEP TWO: Scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scrapers are generally preferred). This will help increase the coverage of 7200 and reduce the amount of liquid generated, and make final clean-up easier.
STEP THREE: If necessary, protect walls, drains, cracks, and other flooring with plastic and absorbent (rags, kitty-litter or sawdust) to keep liquified adhesive contained.
STEP FOUR: Reapply 7200 as in step one. Agitate with a short-bristled broom, hand-held or rotating floor scrubber with stripper pads to fully lift and liquefy adhesive residue from the subfloor. This liquid may then be removed with absorbent.
STEP FIVE: Wash and rinse the floor thoroughly with Sentinel Envirowash 805 or Sentinel 810 and water to ensure a clean surface. Allow to dry.



Sentinel Products Inc.
Brooklyn Park, MN 55445
800-373-0633
www.senpro.com