



Sentinel 890 High-Sudsing Industrial Foamer

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/27/2018

Supersedes: All previous versions

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Sentinel 890 High-Sudsing Industrial Foamer

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Used to increase foaming properties of cleaning detergents, use as a dust suppressant

1.3. Details of the supplier of the safety data sheet

Sentinel Products Inc.
8901 Wyoming Avenue North
Brooklyn Park, MN 55445
Phone: (763) 571-0630
Toll-free: (800)-373-0633
www.senpro.com

1.4. Emergency telephone number

Emergency number : 1-866-359-5661

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Corrosion/Irritation Category 2 H315

Eye Irritation Category 1 H318

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H315 - Causes skin irritation
H318 - Causes serious eye damage

Precautionary statements (GHS-US) :

P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection/face protection, protective gloves.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P333+P313 - If skin irritation or rash occurs: get medical advice/attention.
P362 - Take off contaminated clothing and wash before reuse.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P501 - Dispose of contents/container to licensed waste handling facility

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Water	(CAS No) 7732-18-5	Proprietary*

Sentinel 890 High-Sudsing Industrial Foamer

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%
Surfactant Blend	(CAS No) Proprietary*	Proprietary*

*The specific chemical identity and exact percentage of composition has been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN : Rinse and wash with plenty of soap and water. Remove contaminated clothing and shoes and wash before reuse.
- First-aid measures after eye contact : IF IN EYES: Immediately rinse cautiously with water for 15 minutes while holding eyelids open. Remove contact lenses, if present and easy to do so. Continue rinsing. Get medical advice/attention promptly.
- First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get medical advice/attention promptly.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be fatal if swallowed and enters airways.
- Symptoms/injuries after inhalation : Inhalation in high concentrations may cause irritation of the upper respiratory tract. Aspiration of this material into the lungs may cause chemical pneumonia or death.
- Symptoms/injuries after skin contact : Contact may cause irritation or an allergic skin reaction. Persons with a pre-existing skin condition may be more susceptible to the effects of this product.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating. May cause burns and possible corneal damage.
- Symptoms/injuries after ingestion : Irritating to the mucous membranes of the mouth, throat, esophagus and stomach.
- Chronic symptoms : No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical. Carbon dioxide. Foam.

5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

Sentinel 890 High-Sudsing Industrial Foamer

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Foam may be used to suppress vapors.
- Methods for cleaning up : Mop up spills and flush residues with large volume of water, or soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. Do not allow product to freeze as container may burst.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Surfactant Blend (Proprietary*)	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established

Ethanalamines, 2,2'-iminobisethanol (111-42-2)	
Remark (ACGIH)	2 mg/m ³
Remark (US OSHA)	15 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas. It is suggested that there be a source of clean water near by should it be needed for flushing eyes.
- Personal protective equipment : Gloves. Protective goggles. Respiratory protection of the dependent type may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.



- Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur or if pre-existing skin conditions are present. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
- Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.
- Skin and body protection : Wear suitable protective clothing as necessary.
- Respiratory protection : An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear

Sentinel 890 High-Sudsing Industrial Foamer

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: None
Odor	: Slight, characteristic
Odor Threshold	: No data available
pH	: 8.0 - 9.0
Relative evaporation rate (butyl acetate=1)	: Slower than ether
Melting point	: No data available
Freezing point	: No data available
Boiling point	: >100 °C (212 °F)
Flash point	: None to boiling
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Freezing.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon Dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Surfactant Blend (Proprietary*)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 6300 mg/kg
LD50 Inhalation rat	> 50 ml/L

Ethanolamines, 2,2'-iminobisethanol (111-42-2)	
LD50 oral	> 680 mg/kg
LD50 dermal	> 8180 mg/kg

Sentinel 890 High-Sudsing Industrial Foamer

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanolamines, 2,2'-iminobisethanol (111-42-2)

LC50 Inhalation	> 20 mg/L
-----------------	-----------

Skin corrosion/irritation	: Causes skin irritation
Serious eye damage/irritation	: Causes eye damage
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Inhalation in high concentrations may cause irritation of the upper respiratory tract. Aspiration of this material into the lungs may cause chemical pneumonia or death.
Symptoms/injuries after skin contact	: Contact may cause irritation or an allergic skin reaction. Persons with a pre-existing skin condition may be more susceptible to the effects of this product.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating. May cause burns and possible corneal damage.
Symptoms/injuries after ingestion	: Irritating to the mucous membranes of the mouth, throat, esophagus or stomach.
Chronic symptoms	: No data available.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : Cleaning Compound

Department of Transportation (DOT) Hazard Classes : Not Regulated

Transport by sea

No additional information available

Sentinel 890 High-Sudsing Industrial Foamer

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

No additional information available

In accordance with ADR / RID / IMDG / IATA / ADN

SECTION 15: Regulatory information

15.1. US Federal regulations

Sentinel 890 High-Sudsing Industrial Foamer

All chemical substances in this product are listed or exempt from listing in the EPA (Environmental Protection Agency) TSCA (Toxic Substances Control Act) Inventory

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

15.2. International regulations

CANADA

No additional information available

15.3. US State regulations

California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Ethanolamines, 2,2'-iminobisethanol (111-42-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

SECTION 16: Other information

Indication of changes : Revision 1.1 - 27 February 2018 – Section 2 Updated

Other information : Author. KAD

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 1

Flammability : 0

Physical : 0

Personal Protection :

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.