

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

24-7

INTERIOR/EXTERIOR PREMIUM COATING

MOLD & MILDEW RESISTANT COATING

Inhibits the growth of bacteria, mold & mildew that cause stains and odors on the coating film.

24-7 is self-priming and can be used on most interior and exterior surfaces.

Use on painted surfaces, wood, concrete, drywall, plaster, brick, and most metals.

Low V.O.C. formula meets the requirements for LEED® EQ Credit 4.2, low-emission materials; paints and coatings.

10-Year limited warranty against the visible growth of mold or mildew.

WHITE



PRODUCT DESCRIPTION

SENTINEL 24-7 COATING WITH ANTIMICROBIAL PRODUCT PROTECTION is a premium quality coating that represents a new generation of environmentally friendly products. 24-7 offers excellent hide, scrubability, flow, and leveling with virtually no odor. This product is designed for use on a variety of surfaces, including previously painted surfaces, wood, concrete, drywall, plaster, brick, and most metals. For wooden, galvanized metal, and surfaces that require a primer, 24-7 is self-priming and a light precoat will prime these surfaces. This product is excellent for use in interior/exterior building applications, including office buildings, schools, apartments, hospitals, warehouses and homes.

LIMITED WARRANTY

Sentinel Products Inc. warrants this product to perform satisfactorily when used in accordance with label directions. Sentinel Products Inc. will replace the product or refund the purchase price in the event this product is proven defective, which shall be the exclusive remedy under the warranty. Liability for consequential damages is specifically excluded. No other warranties expressed or implied are given.

WARNING

THIS PRODUCT COMPLIES WITH FEDERAL LAW RESTRICTING THE PRESENCE OF LEAD IN CONSUMER COATINGS. REMOVAL OF OLD PAINT BY SANDING, SCRAPING, OR OTHER MEANS MAY GENERATE DUST OR FUMES WHICH CONTAIN LEAD. EXPOSURE TO LEAD DUST OR FUMES MAY CAUSE ADVERSE HEALTH EFFECTS ESPECIALLY IN CHILDREN OR PREGNANT WOMEN. CONTROLLING EXPOSURE TO LEAD OR OTHER HAZARDOUS SUBSTANCES REQUIRES THE USE OF PROPERLY FITTED RESPIRATOR (NIOSH-APPROVED) AND PROPER CONTAINMENT AND CLEAN UP. FOR ADDITIONAL INFORMATION, CONTACT THE USEPA/LEAD INFORMATION HOTLINE AT 1-800-424-LEAD (5323), OR VISIT THE EPA'S SITE AT WWW.EPA.GOV/LEAD

THIS PRODUCT MUST NOT BE ALLOWED TO FREEZE. DO NOT APPLY IN TEMPERATURES BELOW 50°F. IN COLDER ENVIRONMENTS, BRING PRODUCT UP TO NORMAL ROOM TEMPERATURE BEFORE USING. DO NOT THIN THIS PRODUCT.

HEALTH AND ENVIRONMENT

This product is lead free and mercury free. It contains no crystalline silica. Material Safety Data Sheets are available upon request, or at www.senpro.com. When spraying, use suitable respiratory protection and provide adequate ventilation. Disposal of most latex paints is allowable in landfills, if the material is in solid form. Always check local regulations before disposing of any product.

ANTIMICROBIAL PRODUCT PROTECTION

SENTINEL 24-7 COATING contains antimicrobial product protection. This unique additive will inhibit the growth of stain and odor causing bacteria, mold, mildew, and other fungal growth on the dried coating film. Microban protection provides an added level of protection between cleanings, but does not take the place of normal cleaning and disinfecting procedures and will not protect users or others against foodborne illness.

APPLICATION

Stir contents thoroughly before and during use. Apply a full generous coat. 24-7 may be brushed, rolled, or sprayed with an airless sprayer using a .015-.019 tip. Keep a "wet" edge, not allowing paint to dry in the middle of the area being painted. This will help avoid lap marks and assure proper coverage.

SURFACE PREPARATION

All surfaces must be clean and dry. Remove all rust, dirt, dust, oil, grease, mold, mildew, and other contaminants from the surface to be painted. Block filler, as a primer may be needed for porous concrete or block. Allow new concrete to cure for 30 days prior to painting. Ferrous metal surfaces that are rusty require a suitable metal primer.

COVERAGE

On smooth surfaces expect greater than 300 sq. ft./gallon and less on more porous surfaces. A second application may be necessary. Coatings applied at 90° to each other generally ensure a smooth and consistent application. To assure proper antimicrobial protection, it is vitally important that all surfaces be completely coated with 24-7.

DRY TIME

This latex product will be dry to the touch in 30 minutes and may be recoated in one hour under most environmental conditions. Allow for longer drying times in areas of high humidity or dampness.

THINNING/TINTING

Do NOT thin this product with mineral spirits or paint thinner. 24-7 comes ready to use. 24-7 may be tinted to pastel with universal colorant systems. Colorant loading to a maximum of 4 oz./gallon.

CLEAN UP

Clean painting tools and spills with warm soapy water while product is still wet. Any spills or splatters should be cleaned up immediately with a wet, soapy cloth. Dried paint may be removed using Sentinel 205 Paint Stripper.

NOTICE

While this product contains few solvents, some colorants used to tint desired colors may contain small amounts of solvents. Even so, this paint would contain the lowest levels of V.O.C.'s available in most paints today.



WARNING

(Contains: Titanium dioxide, Nepheline syenite, Propylene glycol, Acrylic copolymer containing (2-methylacrylic acid, aqua ammonia), Zinc pyrithione)

HAZARD STATEMENTS: Causes eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Avoid breathing spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye protection, protective clothing, face protection, protective gloves. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice. If on skin: wash with plenty of soap and water. If skin irritation occurs: get medical attention. Take off contaminated clothing and wash it before reuse. If exposed or concerned, get medical advice. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID: EYES- IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing. IF ON SKIN: Wash with plenty of water. IF INHALED: Move person to fresh air. IF SWALLOWED: Rinse mouth. Seek medical attention.

HANDLING AND STORAGE: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep container closed when not in use. Keep from freezing. REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY

FORMULA
24-7

LOW ODOR FORMULA
INTERIOR/EXTERIOR USE
GREAT COVERAGE RATES & EASY TO APPLY

KEEP OUT OF REACH OF CHILDREN

For special instructions or additional information, contact Sentinel at: 800-373-0633 or visit us at www.senpro.com.



Sentinel Products, Inc.
8901 Wyoming Ave. N.
Brooklyn Park, MN 55445
800-373-0633
www.senpro.com