

PROFESSIONAL RESTORATION PRODUCTS

FORMULA

537

**MULTI-SURFACE
SEALER/PRIMER
LOW VISCOSITY FORMULA
TRAPS ODORS
WATER-BASED**

SEALER/PRIMER
LOW VISCOSITY
ODOR ENCAPSULANT



1 U.S. Gallon (3.79L)

CAUTION: MAY CAUSE EYE & SKIN IRRITATION.
Read precautions on back panel.

pH 4.0 - 4.5

PROFESSIONAL RESTORATION PRODUCTS

Sentinel 537 Low Viscosity Sealer/Primer Odor Encapsulant is a professional strength, low-odor, fast-drying sealer encapsulant used to seal and trap odors commonly found on restoration projects like smoke and other odors. Sentinel 538 works great as part of a two-part system and should be used after affected areas have been cleaned and treated with Sentinel 522 Smoke & Odor Cleaner & Destroyer or Sentinel 531 Smoke & Odor Counteractant. 537 has a pH of 8.5 - 9.5.

Surface Preparation: New Work: Surface must be clean and dry. Remove all dust, dirt and similar residue. Newly plastered walls must be allowed to dry thoroughly before coating. On new wood, surface should be lightly sanded and dusted. Seal any knots or resinous areas thoroughly. Old Work: Clean surface completely. Remove all old loose paint, grease, oil, dirt, wax, and any other contaminants. Lightly sand glossy areas. Spot prime and sand all patched areas. Masonary: Allow all new masonry surfaces adequate cure time before application of this product. Remove any efflorescence. Apply only to a clean, dry surface. Two coats are recommended. For best results the application area should be at least 60° F with humidity levels below 70%. Coverage rates average around 400 square feet per gallon, depending on the porosity of the surface being coated. Shake or stir 537 thoroughly before using.

Directions for Use: (For Professional Use Only.) Apply Sentinel 537 using a brush, medium nap roller, or sprayer. Apply a thin uniform coat. 537 will dry clear. When spraying 537, mix contents thoroughly, and use a .020 tip. Allow 537 to dry thoroughly (a minimum of 120 minutes). If necessary, a second coat can be applied after firstcoat is completely dry. If spraying 537 in HVAC ducts or systems, allow to dry for 2 hours before recirculating fresh air. Fresh air should be carefully inspected for odors before ventilating into occupied spaces. The use of an MSHA /NIOSH-approved respirator is recommended when exposed to spray mists or in areas of poor ventilation. 537 goes on white but will dry clear.

Clean Up: Undried product and painting equipment can be cleaned with soap and water while 537 is still wet. Dried product can be removed using Sentinel 205 Paint & Varnish Stripper.

FOR USAGE QUESTIONS OR ADDITIONAL INFORMATION, CONTACT SENTINEL CUSTOMER SERVICE AT 1-800-373-0633 OR VISIT US ON THE WEB AT www.senpro.com.

CAUTION: KEEP OUT OF REACH OF CHILDREN. May cause eye and skin irritation. Do not use this product in a manner inconsistent with the directions for use. Avoid contact with eyes and skin. Keep container closed when not in use. Store and transport in upright position. KEEP FROM FREEZING.

FIRST AID: If taken internally, do NOT induce vomiting and call physician immediately. In case of eye contact, flush thoroughly with water and seek medical attention. For skin contact, wash thoroughly with soap and water.

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.

Manufactured by: Sentinel Products, Inc.
8901 Wyoming Ave. N., Brooklyn Park, MN 55445
1-800-373-0633 or www.senpro.com

