

FORMULA

539

Anti-Microbial Product Protection
Multi-Surface Sealer/Primer
Stain Blocking Formula

*This sealer contains a fungistatic agent which inhibits the growth of mold and mildew on the dried surface of the sealer.

SEALER/PRIMER
ODOR ENCAPSULANT
STAIN BLOCKER

WHITE



FORMULA

539

Anti-Microbial Product Protection
Multi-Surface Sealer/Primer
Stain Blocking Formula

PRODUCT DESCRIPTION

Sentinel 539 Sealer/Primer Odor Encapsulant is a professional strength, low-odor, fast drying encapsulant used to seal surfaces and lock down odors found in new construction, remodeling, and on fire and water damage restoration projects. Sentinel 539 can be used to block the odors associated with smoke damage, mold and mildew, urine and other biological/animal odors. Sentinel 539 provides the additional benefit of inhibiting the growth of mold and mildew on the dried sealer surface when used as a topcoat.*

WARRANTY NOTICE

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.

WARNING!

If you scrape, sand, or remove old paint, you may remove lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING

(Contains: Titanium dioxide)
Suspected of causing cancer.

HAZARD STATEMENTS:

PRECAUTIONARY STATEMENTS:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye protection, protective clothing, protective gloves. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to licensed waste handling facility.
FIRST AID: EYES- IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing. IF SWALLOWED: Rinse mouth thoroughly. Do NOT induce vomiting without advice from Poison Control Center or medical professional. Get medical attention if you feel unwell.
HANDLING AND STORAGE: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep container closed when not in use. REFER TO SDS FOR MORE INFORMATION
FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

SURFACE PREPARATION

For New Work: Surface must be clean and dry. Remove all dust, dirt and similar residue. Newly plastered walls must be allowed to dry thoroughly before coating. On new wood, surface should be lightly sanded and dusted. Seal any knots or resinous areas thoroughly.
Old Work: Clean surface completely. Remove all loose old paint, grease, oil, dirt, wax and other contaminants. Lightly sand glossy areas. Spot prime and sand all patched areas.
Masonry: Allow all new masonry surfaces adequate cure time before application of this product. Remove any efflorescence. Apply only to a clean, dry surface. Two coats are recommended. Shake or stir 539 thoroughly before using.

DIRECTIONS FOR USE

Apply Sentinel 539 using a brush, roller or airless sprayer with a .015 - .020 tip. Apply a thin, uniform coat. Allow 539 to dry thoroughly. If necessary, a second coat can be applied after the first coat is completely dry. Allow the second coat to dry completely before painting or applying other products. NOTE: Sentinel 539 will lose its anti-microbial product protection if it is NOT the topcoat
For best results the application area should be at least 50° F with humidity levels below 90%. Store indoors.



HAZARD RATING: HMIS
HEALTH 1
FLAMMABILITY 0
REACTIVITY 0
PERSONAL PROTECTION A

