



## PRODUCT DATA SHEET

### FORMULA 7200

# NO ODOR MASTIC REMOVER

NO ODOR / OVER 200° F FLASPOINT / V.O.C. COMPLIANT

## Product Description

Sentinel 7200 No Odor Mastic Remover is formulated with a flashpoint greater than 200° F and is designed to clean and remove black asphalt and solvent based mastics in odor sensitive areas such as schools, high rises, hospitals, government and residential buildings.

## Application Information (Always follow product label instructions for best results)

### DIRECTIONS:

Before beginning work, protect all walls, flooring, carpeting, cracks or wood with an absorbent from liquid materials. This will ensure easier clean-up and eliminate potential problems

### STEP 1:

Wet the entire adhesive surface with 7200. This may be done by spraying or mopping 7200 over the surface of the mastic. Allow 7200 to soak and penetrate into the mastic for 10 - 20 minutes.

### STEP 2:

Scrape or squeegee the bulk of the softened or liquefied mastic from the surface with a floor scraper (razor scraper) or floor squeegee.

### STEP 3:

Reapply 7200 as in step one. Agitate with a short-bristled broom, hand-held or rotating floor scrubber with stripper pads to fully lift and liquefy adhesive residue from the subfloor. The liquid may then be removed with absorbent.

### STEP 4:

Wash and rinse the floor thoroughly with Sentinel 805 and water to ensure a clean surface. Allow to dry a minimum of 24 hours before installing new flooring.

### COVERAGE:

Expect coverage rates of 100-200 sq. feet per gallon.

### V.O.C. CONTENT:

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

### WARRANTY NOTICE:

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

HAZARD RATING: HMIS  
HEALTH 1  
FLAMMABILITY 1  
REACTIVITY 0  
PERSONAL PROTECTION H

## PROPERTIES

Physical state: Liquid

Appearance: Clear

Color: None to amber

Odor: Mild Solvent Odor

pH: Not Applicable

Boiling Point: 363-381° F.

Flash Point: 200° F.

Self Ignition Temperature: 421° F.

Vapor Pressure: <0.5 mm Hg@68° F.

VOC Content: <15g/l\*

\* When determining VOC content in accordance with the requirements set forth by the Ozone Transport Commission (OTC), effective 01-01-2009

# 7200 NO ODOR MASTIC REMOVER

**V.O.C. COMPLIANT**

## **SENTINEL 7200 NO ODOR MASTIC REMOVER**

Sentinel 7200 No Odor Mastic Remover is formulated with a flashpoint greater than 200° F and is designed to clean and remove black asphalt and solvent based mastics in odor sensitive areas such as schools, high rises, hospitals, government and residential buildings.



**No Odor / Over 200° F Flashpoint / Fast-Acting**

**800-373-0633 or [www.senpro.com](http://www.senpro.com)**

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445