

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 12/08/2015 Supersedes: All previous versions Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: Sentinel 532 Solvent Based Counteractant

Product name Product form

: Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Odor Counteractant for thermal fogging applications

1.3. Details of the supplier of the safety data sheet

Sentinel Products Inc. 8901 Wyoming Avenue North Brooklyn Park, MN 55445 Phone: (763) 571-0630 Toll-free: (800)-373-0633 www.senpro.com

1.4. Emergency telephone number

Emergency number

: 1-866-359-5661

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flammable Liquid Category 4	H227
Aspiration Toxicity Category 1	H304
Skin Irritation Category 2	H315
Skin Sensitization Category 1	H317
Eye Irritation Category 2	H319
Specific Target Organ Toxicity (Single Exposure) [Narcotic	H336
effects] Category 3	
Chronic Aquatic Toxicity Category 2	H411

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)

	GHS07 GHS08 GHS09
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 H227 - Combustible liquid H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS-US)	 P210 - Keep away from heat, open flames, sparks No smoking P261 - Avoid breathing mist/vapors/spray. P271 - Use only outdoors or in a well ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace P264 - Wash hands thoroughly after handling. P280 - Wear eye protection, protective clothing, protective gloves P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell P273 - Avoid release to the environment. P391 - Collect spillage.

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: Use dry chemical, foam, CO2 for extinction

P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste handling facility

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	Proprietary*
Proprietary Fragrance Blend	(CAS No) (Mixture)	Proprietary*
*The exact product identification and/or percentage of composition has been withheld as a trade secret		

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).	
First-aid measures after inhalation	: IF INHALED: If breathing difficulties, dizziness, or light headedness occur when working in areas with high vapor concentation, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing stops, begin artificial respiration and seek immediate medical attention.	
First-aid measures after skin contact	: IF ON SKIN: Remove contaminated clothing. Immediately rinse with plenty of mild soap and water (for at least 15 minutes). If skin irritation occurs, get medical advice/attention.	
First-aid measures after eye contact	: IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation occurs, get medical advice/attention.	
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Obtain emergency medical attention.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/injuries	: May be fatal if swallowed and enters airways.	
Symptoms/injuries after inhalation	: Inhalation of excessive concentration of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue). Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties due to the irritant properties of the material.	
Symptoms/injuries after skin contact	 Contact may cause irritation. Prolonged or repeated exposure to this material may cause redness, burning, drying or cracking of the skin or dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of this material. 	
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating. May cause burning, tearing or redness.	
Symptoms/injuries after ingestion	: Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue.) Acute exposure to these compounds results in narcosis, pulmonary edema, and severe kidney and liver damage.	
Chronic symptoms	: No data available.	
4.3. Indication of any immediate medic	al attention and special treatment needed	

No additional information available

SECTION 5: Firefighting measures		
5.1.	Extinguishing media	
Suitabl	e extinguishing media	: Dry chemical. Carbon dioxide. Foam.
5.2.	Special hazards arising from	n the substance or mixture
Fire ha	zard	: This material is an NFPA IIIA combustible liquid.
Explos	ion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactiv	vity	: No dangerous reactions known under normal conditions of use.
5.3.	Advice for firefighters	
Firefigh	nting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
Protect	tion during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
12/08/2	015	Sentinel 532 Solvent Based 2/6 Counteractant

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures			
6.1.	Personal precautions, protective e	equipment and emergency procedures	
Genera	l measures	: Evacuate area. Keep upwind. Ventilate area. Keep all sources of ignition and hot metal surfaces away from spill. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).	
6.1.1.	For non-emergency personnel		
Protect	ive equipment	: Wear Protective equipment as described in Section 8.	
Emerge	ency procedures	: Evacuate unnecessary personnel.	
6.1.2.	For emergency responders		
Protect	ive equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.	
6.2.	Environmental precautions		
 Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. 6.3. Methods and material for containment and cleaning up 		tify authorities if liquid enters sewers or public waters. Avoid release to the environment.	
		ment and cleaning up	
For cor	tainment	 Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Foam may be used to suppress vapors. 	
Method	s for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).	
6.4.	Reference to other sections		
No additional information available SECTION 7: Handling and storage			
7.1.	Precautions for safe handling		
Precau	tions for safe handling	: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking.	

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
Remark (ACGIH)	OELs not established	
Remark (US OSHA)	OELs not established	

Keep container closed when not in use.

Proprietary Fragrance Blend (Mixture)		
Remark (ACGIH)	OELs not established	
Remark (US OSHA)	OELs not established	

8.2. Exposure controls

Appropriate engineering controls Personal protective equipment

- : Ensure adequate ventilation, especially in confined areas.
- : Gloves. Protective clothing. Protective goggles. Respiratory protection of the dependent type.

: Keep only in the original container in a cool, well ventilated place away from : Heat sources.



- : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
- : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

12/08/2015

Hand protection

Eye protection

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection	: It is suggested a source of clean water be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.
Respiratory protection	: An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Appearance	: Clear
Color	: None
Odor	: Solvent Citrus
Odor Threshold	: No data available
рН	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212.75 °C (415 °F) Note: Minimum.
Flash point	: 76.6 °C (170 °F) Note: Minimum. Method: PMCC
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.1 mm Hg at 68 °F
Relative vapor density at 20 °C	: Heavier than air.
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Sparks. Heat. Open flame.

10.5. Incompatible materials

Avoid contact with : Strong oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Petroleum distillates, hydrotreated light (64742-47-8)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h	

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

-			
	Skin corrosion/irritation	:	Causes skin irritation
	Serious eye damage/irritation	:	Causes eye irritation
	Respiratory or skin sensitization	:	Skin sensitizer
	Germ cell mutagenicity	:	Not classified
	Carcinogenicity	:	Not classified
	Reproductive toxicity	:	Not classified
	Specific target organ toxicity (single exposure)	:	Not classified
	Specific target organ toxicity (repeated		Not classified
	exposure)		
	Aspiration hazard	:	May be fatal if swallowed and enters airways.
	Symptoms/injuries after inhalation	:	Inhalation of excessive concentration of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue). Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties due to the irritant properties of the material.
	Symptoms/injuries after skin contact	:	Contact may cause irritation. Prolonged or repeated exposure to this material may cause redness, burining, drying or cracking of the skin or dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.
	Symptoms/injuries after eye contact	:	Direct contact with the eyes is likely to be irritating. May cause burning, tearing or redness.
	Symptoms/injuries after ingestion	:	Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue.) Acute exposure to these compounds results in narcosis, pulmonary edema, and severe kidney and liver damage
	Chronic symptoms	:	No data available.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.	

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: Cleaning Compound
Department of Transportation (DOT) Hazard Classes	: Not Regulated
Other information	: Not regulated in pkg. of less than 119 gal.

Transport by sea

No additional information available

Air transport

No additional information available

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

In accordance with ADR / RID / IMDG / IATA / ADN

SECTION 15: Regulatory information	on	
15.1. US Federal regulations		
Sentinel 532 Solvent Based Counteractant		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard	
Petroleum distillates, hydrotreated light (6	4742-47-8)	
Listed on the United States TSCA (Toxic Sub	stances Control Act) inventory	

15.2. International regulations

CANADA

Petroleum distillates, hydrotreated light (64742-47-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

No additional information available

15.2.2. National regulations

Petroleum distillates, hydrotreated light (64742-47-8)	
Listed on Inventory of Existing Chemical Substances (IECSC)	
Listed on the AICS (the Australian Inventory of Chemical Substances)	
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.	
Listed on the Korean ECL (Existing Chemical List) inventory.	

15.3. US State regulations

California Proposition 65

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION	16:	Other	information
---------	-----	-------	-------------

Indication of changes Other information	 Revision 1.0 – 08 December 2015 - New SDS Created. Author. KAD
NFPA health hazard	: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard	: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

HMIS III Rating		
Health	:	1
Flammability	:	2
Physical	:	0
Personal Protection		

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.