

F O R M U L A

206

PEROXYStrip  
PAINT & COATING STRIPPER

PRODUCT DESCRIPTION

Sentinel 206 PeroxyStrip is an environmentally safe stripper, powerful enough to dissolve most paints and coatings. PeroxyStrip is formulated with non-hazardous ingredients and is boosted with the power of hydrogen peroxide. PeroxyStrip's thick gel allows for easy use, especially on vertical surfaces and it rinses with water, making for fast clean up. This low odor, nonflammable formula is safe for both interior and exterior projects.

WARRANTY NOTICE

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.



DANGER

(Contains: Benzyl Alcohol, Hydrogen Peroxide, 2-(2-butoxyethoxy), Polymer Blend, Surfactant Blend)

HAZARD STATEMENTS: Causes skin irritation. Causes serious eye damage  
PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves.  
IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents /container to licensed waste handling facility.  
FIRST AID: EYES- IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). get medical advice/ attention.Skin- IF ON SKIN: immediately rinse with water (for at least 15 minutes). Get medical advice/attention. Inhalation- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. Ingestion- IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Obtain emergency medical attention.  
HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. REFER TO SDS FOR MORE INFORMATION

REFER TO SDS FOR MORE INFORMATION

KEEP OUT OF REACH OF CHILDREN

F O R M U L A

206

HAZARD RATING: HMIS  
HEALTH 1  
FLAMMABILITY 0  
REACTIVITY 0  
PERSONAL PROTECTION A

PREPARATION

Remove all loose or peeling coating with scraper or by pressure washing. Always perform a test in a small inconspicuous area to ensure desired results.

DIRECTIONS FOR USE

Step 1: Apply product generously with rags, brushes or putty knife.  
Step 2: Let 206 penetrate the coating: Varnish, Shellac, Lacquer: 30-60 minutes. Latex/Oil based paints, polyurethane, multi layered finishes: 15 minutes - 1 + hours. For difficult to remove multi-layered coatings, allow 206 to penetrate overnight. Dwell time varies on the thickness of the coating.  
Step 3: Test a small area of the surface with a putty knife to see if the finish has softened. If not, let the 206 sit longer.  
Step 4: Remove 206 immediately after finish has softened by gently scraping with a stripping tool/ putty knife. When removing multiple layers of coating, a second coat of 206 may be necessary.  
Step 5: Remove any remaining softened finish with a stripping pad dampened with soapy water. When stripping on a wood surface, always rub in direction of the grain.  
Step 6: Clean any excess 206 with a dampened with clean water or mineral spirits.  
Step 7: Wipe surface with a dry, clean cloth. Let surface dry thoroughly before refinishing.  
Step 8: Dispose of in accordance with federal, state & local guidelines DO NOT USE ON PLASTIC OR FIBERGLASS



Sentinel Products Inc.  
Brooklyn Park, MN 55445  
800-373-0633  
www.senpro.com