

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

**620**

CONCENTRATE

**BIODEGRADABLE  
LOW ODOR FORMULA  
HIGHLY CONCENTRATED  
EASILY REMOVES:  
GLUED DOWN CARPET  
SHEET VINYL  
AND CARPET FOAM BACKING**

**CARPET & ADHESIVE  
SHEET VINYL**

**REMOVER**



**PRODUCT DESCRIPTION**

SENTINEL 620™ CARPET & SHEET VINYL ADHESIVE REMOVER is the complete product for easily removing carpeting or for stripping the toughest latex and acrylic adhesives from all floor surfaces. 620™ unique formula works quicker, cleans and removes better and is easier to use than all other remover products.

**WARRANTY NOTICE**

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling, and use, or effect of that use.

**DIRECTIONS**

**REMOVAL OF CARPETING**  
While 620™ works on most latex, acrylic, and pressure sensitive adhesives, it is recommended that you test a small area first. Cut the carpet to be removed in 1 foot strips. Mix 1 part 620™ to 4 parts water. Pour the resulting mixture onto the carpet maintaining even coverage. Depending on the nature of the carpet, coverage of about 35 square ft per gallon should be achieved. Allow to soak 1-4 hours, or overnight if preferred and proceed to pull up carpeting. Protect hands and feet from chemical. Scrape the affected adhesive from the subfloor and rinse. Allow overnight drying before reflooring.

**REMOVAL OF SHEET VINYL BACKING**  
Remove wear layer. Mix 1 part 620™ to 4 parts hot water. Apply mixture to the backing. Desired coverage is about 30 square feet per gallon. (The backing absorbs the solution slowly. It is preferable to apply the solution to wet the backing and in 30 minutes apply the remaining solution). Allow up to 2 hours for the solution to penetrate and then scrape backing from the subfolder. To fully clean the floor, use a broom or stripper pad with rinse water. Allow overnight drying before reflooring.

**REMOVAL OF ADHESIVE**  
620™ is a high strength remover and depending on the nature of the adhesive may be used straight or diluted 1 part 620™ to 4 parts water. First, apply 620™ to the adhesive to be removed. 620™ will begin working in 20 minutes. Some adhesives may take as long as an hour. Once the adhesive is pliable, remove with a scraper and dispose. To fully clean the floor, use a broom or stripper pad with rinse water. Allow overnight drying before reflooring.



**DANGER**

(Contains: 2-aminoethanol, 2-(2-butoxyethoxy) ethanol, Surfactant)

**HAZARD STATEMENTS:** Causes severe skin burns and eye damage.

**PRECAUTIONARY STATEMENTS:** Do not breathe dusts or mists. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves.  
**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (or hair):** Remove immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

**FIRST AID:** **EYES- IF IN EYES:** Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). get medical advice/ attention. **Skin- IF ON SKIN:** immediately rinse with water (for at least 15 minutes). Get medical advice/attention. **Inhalation- IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. **Ingestion- IF SWALLOWED:** Rinse mouth, Do NOT induce vomiting, Obtain emergency medical attention.

**HANDLING AND STORAGE:** Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

FORMULA

**620**

CONCENTRATE

HAZARD RATING: HMIS  
HEALTH 1  
FLAMMABILITY 1  
REACTIVITY 1  
PERSONAL PROTECTION H

FOR SPECIAL INSTRUCTIONS CONTACT  
SENTINEL'S CUSTOMER SERVICE AT 1.800.373.0633  
OR VISIT US AT [www.senpro.com](http://www.senpro.com)

Sentinel Products Inc.  
Brooklyn Park, MN 55445  
800-373-0633  
[www.senpro.com](http://www.senpro.com)