September 4 CLEANER ENVIRONMENT

ICT DESCRIPTION | D

SENTINEL 770 ODORLESS DEGREASER AND ADHESIVE REMOVER is designed to remove asphalt cutback adhesives and rinse leaving no residue. When subfloors are dry, new flooring may be confidently installed.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling, and use, or effect of that use.



(Contains: Petroleum distillates, hydrotreated light, 2-(2butoxyethoxy) ethanol, Alcohol Ethoxylate) May be fatal if swallowed and enters airways.

DIRECTIONS

BLACK CUTBACK ADHESIVE REMOVAL STEP ONE: Wet the entire adhesive surface with 770. This may be done by using a garden sprayer or by mopping 770 over the surface of the adhesive. DO NOT over apply 770 in the first step. Allow 770 to soak and penetrate for 10-20 minutes. STEP TWO: Scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scrapers are generally preferred). This will help increase the coverage of 770 and reduce the amount of liquid generated, and make final cleanup easier. STEP THREE: If necessary, protect walls, drains, cracks, and other flooring with plastic and absorbent (rags, kitty litter or sawdust) to keep liquefied adhesive contained.

STEP FOUR: Reapply 770 as in step one. Agitate with a short bristled broom, hand held or rotating floor scrubber with stripper pads to fully lift and liquefy adhesive residue from the subfloor. This liquid may then be removed with an absorbent. STEP FIVE: Wash and rinse the floor thoroughly with Sentinel EnviroWash 805.

HAZARD STATEMENTS: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents /container to licensed waste handling facility.

FIRST AID: EYES- IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). get medical advice/ attention. SKIN- IF ON SKIN: immediately rinse with water (for at least 15 minutes). Get medical advice/attention. INHALATION- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. INGESTION- IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION • FOR INDUSTRIAL USE ONLY • KEEP OUT OF REACH OF CHILDREN

HAZARD RATING: HMIS HEALTH 1 FLAMMABILITY 2 REACTIVITY 0 PERSONAL PROTECTION B

FOR SPECIAL INSTRUCTIONS CONTACT SENTINEL'S CUSTOMER SERVICE AT 1.800.373.0633 OR VISIT US AT www.senpro.com



FASTER ACTING

GREATER COVERAGE



Sentinel Products Inc. Minneapolis, MN 55445 800-373-0633 www.senpro.com

07142015

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

ODORLESS FASTER ACTING GREATER COVERAGE

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resoure Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

CARB

