

A high-strength, fast-acting product designed to remove tile & carpet adhesives.

A multi-use product that replaces Citrus Removers.

NEW LOW-ODOR FORMULA!





PRODUCT DESCRIPTION

other low-odor or citrus removal products.

WARRANTY NOTICE

Sentinel 787 HIGH-STRENGTH MASTIC REMOVER is designed to remove asphalt cutback and carpet adhesives

and rinse leaving no residue. 787 is a powerful alternative to

Seller makes no warranty, expressed or implied, nor

accepts any responsibility for any direct or consequential

damages beyond purchase price, because seller cannot

control users handling, and use, or effect of that use.

When subfloors are dry, new flooring may be confidently installed.

DIRECTIONS

ADHESIVE REMOVAL INSTRUCTIONS STEP ONE: If necessary, protect walls, drains. and other flooring with plastic and absorbent (rags, kittylitter or sawdust) to keep liquified adhesive contained.

STEP TWO: Apply 787 to surface of adhesive. This may be done by using a garden sprayer or by mopping 787 over the surface. DO NOT overapply 787 in this step. Allow 787 to soak and penetrate the adhesive for 10-20 minutes.

STEP THREE: For heavier adhesives, scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scrapers are generally preferred). This will help increase the coverage of 787, reduce the amount of liquid generated, and make final clean-up easier.

STEP FOUR: Reapply 787 and agitate with hand-held or rotating floor scrubber with stripper pads or short-bristled brooms to fully lift and liquefy adhesive residue from the subfloor. This liquid may then be removed with absorbent.

STEP FIVE: Wash and rinse the floor thoroughly with Sentinel Envirowash 805 or Sentinel 810 and water to ensure a clean surface Allow surfaces to dry.



(Contains; Petroleum distillates, hydrotreated light, Solvent naphtha, petroleum, heavy aromatic, 2-(2-butoxyethoxy) ethanol, Surfactant) May be fatal if swallowed and enters airways.

HAZARD STATEMENTS: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eve irritation.

PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. f swallowed, do NOT induce vomiting. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID: EYES- IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum), get medical advice/ attention.Skin- IF ON SKIN: immediately rinse with water (for at least 15 minutes). Get medical advice/attention. Inhalation- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. Ingestion- IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION

FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

*V.O.C. Compliant

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

HAZARD RATING: HMIS HEALTH 1 FLAMMABILITY 2 REACTIVITY 0 PERSONAL PROTECTION H

HIGH-STRENGTH FAST-ACTING

GREATER COVERAGE

09212015





Sentinel Products, Inc. 8901 Wyoming Ave. N. Brooklyn Park, MN 55445 800-373-0633

www.senpro.com