

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

GMR

CITRUS MASTIC REMOVER
CITROSOLVE



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

PRODUCT DESCRIPTION

This is a citrus based mastic remover for removing black mastic on asbestos abatement jobs. This material does NOT contain asbestos.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond the purchase price, because seller cannot control user's handling, and use, or effect of use.

HAZARD RATING:	HMS
HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	H



DANGER

(Contains: Petroleum distillates, hydrotreated light, d- Limonene, 2-(2- butoxyethoxy) ethanol, Surfactant)

HAZARD STATEMENTS: Flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction. Causes skin irritation. May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Keep container tightly closed. Ground/-Bond container and receiving equipment. Use explosion- proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN (or hair): Remove/ take off immediately all contaminated clothing. Rinse skin/ hair with water. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. Avoid release to the environment. Collect spillage. IN CASE OF FIRE: Use dry chemical, foam, CO2 for extinction. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/ container to licensed waste handling facility.

FIRST AID: SEE PRECAUTIONARY STATEMENTS & IF INHALED: If breathing difficulties, dizziness or light headedness occur when working in areas with high vapor concentration, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing stops, begin artificial respiration and seek immediate medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breath mists. Keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

DIRECTIONS

STEP ONE: Before beginning work, be sure to protect all walls, flooring, carpeting, cracks, or wood from liquid materials. This will ensure easier cleanup and eliminate potential problems.
STEP TWO: Once the floor tile is removed simply apply product to the adhesive. This may be done by using a mop to evenly distribute the material. Allow the material to soak and penetrate for 10-15 minutes.
STEP THREE: Using scrapers, remove the softened adhesive from the floor surface and reapply to the remaining adhesive residue.
STEP FOUR: Using brooms or floor scrubbers, agitate resulting mixture and remove all liquids using absorbents.
STEP FIVE: Once the mastic and cleaner are removed, all residues may be completely rinsed by washing the floor with a Sentinel 805 EnviroWash and water solution.

01282016



Sentinel Products Inc.
Minneapolis, MN 55432
800-373-0633
www.senpro.com