

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

**SC-170**

LOW ODOR  
FAST ACTING  
GREATER COVERAGE



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

# LOW ODOR MASTIC REMOVER



## PRODUCT DESCRIPTION

SENTINEL SC-170 Low Odor Mastic Remover is designed to remove asphalt cutback adhesives and rinse leaving no residue. When subfloors are dry, new flooring may be confidently installed.

## WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control user's handling, and use, or effect of that use.



## DANGER

(Contains: Petroleum distillates, hydrotreated light, 2-(2-butoxyethoxy) ethanol, Alcohol Ethoxylate)

May be fatal if swallowed and enters airways.

**HAZARD STATEMENTS:** Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

**PRECAUTIONARY STATEMENTS:** Keep away from heat, open flames, sparks. No smoking. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents /container to licensed waste handling facility.

**FIRST AID:** EYES- **IF IN EYES:** Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). get medical advice/ attention. **SKIN- IF ON SKIN:** immediately rinse with water (for at least 15 minutes). Get medical advice/attention. **INHALATION- IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. **INGESTION- IF SWALLOWED:** Rinse mouth, Do NOT induce vomiting. Obtain emergency medical attention.

**HANDLING AND STORAGE:** Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

## DIRECTIONS

**STEP ONE:** Wet the entire adhesive surface with product. This may be done by using a garden sprayer or by mopping SC-170 over the surface of the adhesive. DO NOT overapply. Allow SC-170 to soak and penetrate for 10-20 minutes.

**STEP TWO:** Scrape the bulk of the softened adhesive from the surface with a floor scraper. This will help increase the coverage of SC-170 and reduce the amount of liquid generated and make final clean-up easier.

**STEP THREE:** If necessary, protect walls, drains, cracks, and other flooring with plastic and absorbent (rags, kitty litter or sawdust) to keep liquified adhesive contained.

**STEP FOUR:** Reapply SC-170 as in Step One. Agitate with a short-bristled broom, hand held or rotating floor scrubber with stripper pads to fully lift and liquefy adhesive residue from the floor. This liquid may then be removed with an absorbent.

**STEP FIVE:** Wash and rinse the floor thoroughly using Sentinel 805 Envirowash or soap and water solution.



FOR SPECIAL INSTRUCTIONS CONTACT  
SENTINEL'S CUSTOMER SERVICE AT 1-800-373-0633  
OR VISIT US AT [www.senpro.com](http://www.senpro.com)  
#07072015

HAZARD RATING: HMIS	
HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	B

## FORMULA

**SC-170**

**Sentinel**  
Products, Inc.  
BETTER SOLUTIONS FOR A CLEANER ENVIRONMENT  
Sentinel Products, Inc.  
Brooklyn Park, MN 55445  
800-373-0633  
[www.senpro.com](http://www.senpro.com)