



PRODUCT DATA SHEET

- LOWER LIMITS
- NEW DILUTIONS
- UPDATED DIRECTIONS

FORMULA 805 ENVIROWASH

CONCENTRATED / CLEANS LEAD DUST / ASPHALT ADHESIVE CLEANUP

Product Description

Sentinel 805 Envirowash is a concentrated product specifically formulated for final preparation of sub floors following mastic removal on asbestos jobs and lead dust cleanup.

Application Information (Always follow product label instructions for best results)

Usage Guidelines:

Read directions and review sds prior to use. Test in a small inconspicuous area prior to using on soft goods and fabrics to assure desired results.

Directions For Use:

For Asphalt Adhesive Residue Removal: Mix 1 part 805 to 1 part hot water, depending on the amount of residue left a second application of 805 may be necessary following adhesive removal. Pour mixture onto floor to be cleaned. Use a broom, manual stripper pad or rotating floor scrubber with stripper pads to scrub the floor until clean. Wash and rinse the floor, changing the water as needed to ensure a clean surface. Allow to dry before resurfacing.

HAZARD RATING: HMIS
HEALTH 1
FLAMMABILITY 0
REACTIVITY 0
PERSONAL PROTECTION

Directions For Use:

For Lead Abatement: Mix 1 part 805 with up to 4 parts of hot water (approximately 1 gallon of 805 to 4 gallons of water). 805 should be used before encapsulating, after active abatement has concluded and for general maintenance in reducing exposure to lead dust.

Procedure: Wash all surfaces, ceilings, walls, floors, windows, doors, fixtures, cabinets, etc. with 805 Envirowash solution. Starting with the ceiling, work down to the floor. The cleaning solution should be changed (at least) after each room has been washed and more often in larger areas. Each time the mixture is changed, workers must ensure that the used water does not re-contaminate the environment. 805 may be applied with sprayers, towels, rags or mops, depending on the area to be cleaned. Use Sentinel Envirotowels for clearance, if cross-contamination, mixing, diluting or lack of water is a problem. Protect exposed skin and eyes, especially when working overhead. Rinse if necessary.

PROPERTIES

Physical state: Liquid

Appearance: Clear

Color: None

Odor: None

pH: 11-12

Boiling Point: >212° F.

Flash Point: None to boiling





805 ENVIROWASH

SENTINEL 805 ENVIROWASH

Sentinel 805 Envirowash is a concentrated product specifically formulated for final preparation of sub floors following mastic removal on asbestos jobs and lead dust cleanup.



Concentrated / Removes Lead Dust / Asphalt Adhesive After Wash

800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445