



FORMULA 626
CARPET & SHEET VINYL ADHESIVE REMOVER
 LOW ODOR / NON FLAMMABLE / NON HAZARDOUS

Product Description

Sentinel 626 Carpet & Sheet Vinyl Adhesive Remover is a powerful, water-based, biodegradable formulation designed specifically for quickly removing latex, acrylic and pressure sensitive adhesives from concrete, terrazzo, ceramic and vinyl tile or wood substrate.

Application Information (Always follow product label instructions for best results)

DIRECTIONS:

REMOVAL OF LATEX, ACRYLIC AND PRESSURE SENSITIVE ADHESIVES:

Step 1: Apply 626 directly onto adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the surface wet. Allow 626 to soak and penetrate for 30-60 minutes.

Step 2: Scrape softened adhesive from the floor with a razor scraper. Repeat steps 1 and 2 if necessary. Dispose of all waste.

Step 3: Rinse the sub-floor thoroughly with clean water. Allow surface to completely dry.

REMOVAL OF SHEET VINYL/ LINOLEUM BACKING:

Once the wear layer is removed, mix 1 part HOT water to 4 parts 626 and apply directly to the remaining backing. Maintain even coverage and a wet surface for 1-2 hours or until backing/ adhesive can be easily removed together with a floor scraper. Rinse the surface with clean water and allow to dry.

REMOVAL OF CARPETING:

Using a utility knife, cut the carpeting into 12" strips, making sure to cut through the carpeting to the sub-floor. Mix 2 parts HOT water to 1 part 626 and pour directly onto carpet. Maintain even coverage and completely saturate carpeting. Allow to soak for 4 hours, or overnight. Remove carpet strips and follow latex removal steps for removing remaining adhesive.

COVERAGE:

Expect coverage rate of 70 sq. feet per gallon for adhesive removal.

V.O.C. CONTENT:

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

PROPERTIES

Physical state: Liquid

Appearance: Clear

Color: None

Odor: No Odor

pH: Not Applicable

Boiling Point: 212° F.

Flash Point: None to boiling

* When determining VOC content in accordance with the requirements set forth by the Ozone Transport Commission (OTC), effective 01-01-2009

HAZARD RATING: HMIS
 HEALTH 1
 FLAMMABILITY 0
 REACTIVITY 0
 PERSONAL PROTECTION H



626 CARPET & SHEET VINYL ADHESIVE REMOVER

V.O.C. COMPLIANT

SENTINEL 626 CARPET & SHEET VINYL ADHESIVE REMOVER

Sentinel 626 Carpet & Sheet Vinyl Adhesive Remover is a powerful, water-based, biodegradable formulation designed specifically for quickly removing latex, acrylic and pressure sensitive adhesives from concrete, terrazzo, ceramic and vinyl tile or wood substrates.



Low Odor / Non Flammable / Non Hazardous Solvent

800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445