

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

PL145

LOW ODOR MASTIC REMOVER



*This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, effective 1-1-2009.



PRODUCT DESCRIPTION

Sentinel PL145 LOW ODOR MASTIC REMOVER is designed to remove asphalt cutback adhesives and rinse leaving no residue. When subfloors are dry, new flooring may be confidently installed.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling, and use, or effect of that use.



DANGER

(Contains: Petroleum distillates, hydrotreated light, 2-(2-butoxyethoxy) ethanol, Surfactant) May be fatal if swallowed and enters airways.

HAZARD STATEMENTS: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID: **EYES- IF IN EYES:** Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minute minimum). get medical advice/ attention. **Skin- IF ON SKIN:** immediately rinse with water (for at least 15 minutes). Get medical advice/attention. **Inhalation- IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. **Ingestion- IF SWALLOWED:** Rinse mouth, Do NOT induce vomiting. Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. do not breath mists. keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

DIRECTIONS

BLACK CUTBACK ADHESIVE REMOVAL
STEP ONE: Before beginning work, protect all walls, flooring, carpeting, cracks or wood from liquid materials. This will ensure easier cleanup and eliminate potential problems.
STEP TWO: Wet the entire adhesive surface with PL-145. This may be done by using a garden sprayer or by mopping PL-145 over the surface of the adhesive. DO NOT over apply PL-145 in the first step. Allow PL-145 to soak and penetrate for 10-20 minutes.
STEP THREE: Scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scrapers are generally preferred). This will help increase the coverage of PL-145 and reduce the amount of liquid generated, and make final clean-up easier.
STEP FOUR: Reapply PL-145 as in step one. Agitate with a short-bristled broom, hand-held or rotating floor scrubber with stripper pads to fully lift and liquefy adhesive residue from the subfloor. This liquid may then be removed with absorbent.
STEP FIVE: Wash and rinse the floor thoroughly with Sentinel Envirowash 805 or Sentinel 810 and water to ensure a clean surface. Allow to dry.

HAZARD RATING: HMIS
HEALTH 1
FLAMMABILITY 2
REACTIVITY 0
PERSONAL PROTECTION H

FORMULA



For special instructions or additional information, contact Sentinel's Customer Service at 800.373.0633 or Internet: <http://www.senpro.com>.

10222020



Sentinel Products, Inc.
8901 Wyoming Ave. N.
Brooklyn Park MN 55445
800-373-0633
www.senpro.com