

## HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS



## **PRODUCT DESCRIPTION:**

Sentinel 696 is a fast acting, non-etching cleaner, created for use on a variety of metals. 696 easily removes drawing & cutting oils, as well as other contaminants, prior to phosphatizing, anodizing, spot welding or painting. 696 can be used in either spray or tank cleaning applications and is safe to use on all common metals.

## DIRECTIONS: (Always follow product label instructions for best results.)

696 has an operating range of 70-160° F and is free-rinsing.

Dilute 696 with water in accordance with the following suggestions: Light Soils: 2-4 fl. oz. of 696 / gallon of water. Medium Soils: 6-8 fl. oz. of 696 / gallon of water. Heavy Soils: 8-16 fl. oz. of 696 / gallon of water.

## FORMULA



SETTLES METAL FINES SAFE ON COMMON METALS NON-ETCHING FAST CLEANING ACTION



For additional information or assistance with this product, please call Sentinel Customer Service at, 800-373-0633.

SPECIFICATIONS:APPEARANCECLEARSPECIFIC GRAVITY (60°F)1.030pH (1% solution)8.5-9

800-373-0633Sentinel Products, Inc<br/>8901 Wyoming Ave. N.www.senpro.comBrooklyn Park MN 55445

