



PRODUCT DATA SHEET

909 SOYBEAN DEGREASER & MASTIC REMOVER

V.O.C. COMPLIANT

SENTINEL 909 SOYBEAN DEGREASER & MASTIC REMOVER

Sentinel 909 Soybean Degreaser & Mastic Remover is a biodegradable, soybean based solvent cleaner for the removal of black asphalt based mastics, grease, lubricants, inks and other petroleum based residues. 909 is ideal for projects when a biodegradable odorless product is preferred.



Odorless / Biodegradable / V.O.C. Compliant

800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445



PRODUCT DATA SHEET



FORMULA 909

SOYBEAN DEGREASER & MASTIC REMOVER

ODORLESS / BIODEGRADABLE / V.O.C. COMPLIANT

Product Description

Sentinel 909 Soybean Degreaser & Mastic Remover is a biodegradable, soybean based solvent cleaner for the removal of black asphalt based mastics, grease, lubricants, inks and other petroleum based residues. 909 is ideal for projects when a biodegradable odorless product is preferred.

Application Information (Always follow product label instructions for best results)

DIRECTIONS:

Review directions and precautions thoroughly before starting work.

STEP 1:

Protect walls, cabinetry, trim, drains, cracks and adjoining flooring with plastic and/or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.

STEP 2:

Apply 909 to the entire adhesive surface. be sure to apply enough remover to completely penetrate and saturate the adhesive to be removed. Allow 909 to soak and penetrate for 40-60 minutes.

STEP 3:

Agitate the surface with stiff, short bristled brushes or coarse stripper pads. Squeegee or scrape the softened or liquified adhesive into puddles and solidify with an absorbent. Remove absorbed material to a container and dispose of following all local, state and federal regulations.

STEP 4:

If necessary, reapply and repeat steps two and three.

STEP 5:

Wash and rinse the floor thoroughly using Sentinel 805 Envirowash and water or a soap and water solution. Allow subfloor to dry for at least 24 hours and test moisture levels before reflooring.

COVERAGE:

Expect coverage rates of 100-150 sq. feet per gallon.

V.O.C. CONTENT:

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

PROPERTIES:

Physical state: Liquid

Appearance: Clear

Color: None to amber

Odor: Mild Odor

pH: Not Applicable

Boiling Point: 470° F.

Flash Point: 200° F.

Vapor Pressure: <0.1 mm Hg @68° F.

VOC Content: <14g/l*

* When determining VOC content in accordance with the requirements set forth by the Ozone Transport Commission (OTC), effective 01-01-2009

HAZARD RATING: HMIS

HEALTH 1

FLAMMABILITY 1

REACTIVITY 0

PERSONAL PROTECTION H

WARRANTY NOTICE:

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

