

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA 770

ODORLESS
FASTER ACTING
GREATER COVERAGE

ODORLESS ADHESIVE
DEGREASER &

REMOVER



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



5 Gallons (18.927L)



PRODUCT DESCRIPTION

SENTINEL 770 ODORLESS DEGREASER & ADHESIVE REMOVER is designed to remove asphalt cutback adhesives and rinse leaving no residue. When subfloors are dry new flooring can be confidently installed.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond the purchase price because seller cannot control users handling, and use, or effect of that use.

DIRECTIONS

BLACK CUTBACK ADHESIVE REMOVAL
STEP ONE: Protect walls, cabinetry, trim, drains, cracks and adjoining flooring with plastic and or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.
STEP TWO: Wet the entire adhesive surface with 770. This may be done by using a garden sprayer or by mopping 770 over the surface of the adhesive. DO NOT overlap. Allow 770 to soak and penetrate for 10-20 minutes.
STEP THREE: Scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scraper generally preferred). This will help increase the coverage of 770 and reduce the amount of liquid generated. Place in a container for disposal.
STEP FOUR: Reapply 770 as in step one. Agitate with a short-bristled broom, hand-held or rotating floor scrubber with stripper pads to fully lift and liquify adhesive residue from the subfloor. Squeegee the resulting mixture into puddles and solidify with an absorbent. Remove absorbed material to a container and dispose. Follow all local, state and federal regulations when disposing of waste.
STEP FIVE: Wash and rinse the floor thoroughly using Sentinel 805 Envirowash and water or a soap and water solution. Allow subfloor to dry for a minimum of 24 hours and test moisture levels before reflooring.



DANGER

(Contains: Petroleum distillates, hydrotreated light, 2-(2-butoxyethoxy) ethanol, Surfactant) May be fatal if swallowed and enters airways.

HAZARD STATEMENTS: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.
PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - no smoking. Keep only in the original container in a cool, well ventilated place away from: heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION • FOR INDUSTRIAL USE ONLY • KEEP OUT OF REACH OF CHILDREN

FOR SPECIAL INSTRUCTIONS CONTACT SENTINEL'S CUSTOMER SERVICE
AT 800.373.0633 OR VISIT US AT www.senpro.com

HAZARD RATING: HMIS
HEALTH 1
FLAMMABILITY 2
REACTIVITY 0
PERSONAL PROTECTION B



Sentinel Products Inc.
Minneapolis, MN 55445
800-373-0633
www.senpro.com

