

# 813 LS LOCKDOWN SEALANT

## SENTINEL 813 LS LOCKDOWN SEALANT

Sentinel 813 LS Lockdown Sealant is a post-removal lockdown sealant solution. 813 LS is premixed and requires no dilution. 813 LS is essential for use during the mandatory sealing of residual asbestos fibers and dust after removal or building demolition. The translucent blue finish is designed for visual tracking of application coverage.



Low Odor / Fast-Drying / Locks Fibers Down

## 800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445

### PRODUCT DATA SHEET



# FORMULA 813 LS LOCKDOWN SEALANT

## LOW ODOR / FAST-DRYING / LOCKS FIBERS DOWN Product Description

Sentinel 813 LS Lockdown Sealant is a post-removal lockdown sealant solution. 813 LS is premixed and requires no dilution. 813 LS is essential for use during the mandatory sealing of residual asbestos fibers and dust after removal or building demolition. The translucent blue finish is designed to aid in visual tracking of application coverage.

**Application Information** (Always follow product label instructions for best results)

#### **Directions For Use:**

Mix thoroughly before using. Sentinel 813 LS does not require dilution.

Apply with an airless sprayer to all exposed surfaces prior to post-removal air-monitoring.

Apply to sheeting prior to dismantling containment.

#### Coverage:

Expect coverage of up to 400 sq. feet per gallon.

#### **Dry Time:**

Dry time will be affected by environment, temperature and humidity level.

813 LS will be dry to the touch in 1 hour at 70°F with 50% relative humidity.

#### Clean Up:

Clean spray equipment and tools with soap and warm water prior to product drying. Dispose of waste following all Local, State and Federal Regulations.

#### **Precautions & Limitations:**

Follow all Local, State and Federal Regulations concerning the abatement and removal of Asbestos Containing Materials.

Wear PPE appropriate for the asbestos hazards of the job site.

Sentinel 813 LS is NOT a Bridging or Penetratiing Encapsulant and should not be used to encapsulate Asbestos Containing Materials (ACM) in place.

Do not allow product to freeze.

#### **Specifications:**

Physical State: Liquid Appearance: Opaque Color: Blue Odor: Slight Latex pH: 5.5 - 6.5 Boiling Point: >212°F

Flash Point: None to boiling



<sup>\*</sup>Formerly 813LE Lockdown Encapsulant