

840 SURFACTANT WETTING AGENT

SENTINEL 840 SURFACTANT WETTING AGENT

Sentinel 840 Surfactant Wetting Agent is a superior wetting agent designed for use prior to the abatement of asbestos containing materials (ACM). Sentinel 840 saturates fibers and lowers surface tension which aids in reducing the release of fibers and dust during removal.



Water Based / High Penetration Rates / Dilutable

800-373-0633 or www.senpro.com

PRODUCT DATA SHEET



FORMULA 840

SURFACTANT WETTING AGENT

WATER BASED / HIGH PENETRATION RATES / DILUTABLE

Product Description

Sentinel 840 Surfactant Wetting Agent is a superior wetting agent designed for use prior to the abatement of asbestos containing materials (ACM). Sentinel 840 saturates fibers and lowers surface tension which aids in reducing the release of fibers and dust during removal.

Application Information (Always follow product label instructions for best results)

Usage Guidelines:

Read directions and review sds prior to use.

Always adhere to all regulations mandated by OSHA and EPA Guidelines when using this product in the removal of Asbestos Containing Materials (ACM).

Approved respirators and personal protective equipment must be used to prevent inhalation of airborne asbestos fibers.

Store in a dry location with a temperature between 40°F and 90°F. Do not allow the product to freeze or the container may burst.

Dispose of all waste according to applicable Local, State and Federal regulations.

Directions For Use:

Sentinel 840 can be used full strength or diluted. If diluted, Sentinel 840 can be mixed with up to twenty (20) parts water to one (1) part Sentinel 840.

Apply Sentinel 840 directly to the material with an airless sprayer or pump sprayer.

Air monitoring of fiber levels should be observed to determine when reapplication is necessary.

Specifications:

Physical State: Liquid Appearance: Clear Color: None

Odor: None

Surface tension: 28 Dynes/cm²

pH: 7.0 - 8.0

Boiling Point: >212°F Flash Point: None to boiling

