



PRODUCT DATA SHEET

24-7 ZERO WATERPROOFING SEALANT

INTERIOR/EXTERIOR

SENTINEL 24-7 ZERO WATERPROOFING SEALANT

Sentinel Mold & Mildew Resistant Waterproofing Sealant is a 100% acrylic water based, antimicrobial coating formulated to stop water penetration through masonry materials. For interior and exterior, above or below grade, vertical applications. Sentinel Mold & Mildew Resistant Waterproofing Sealant withstands 35 PSI of water pressure preventing moisture transmission into basements, crawlspaces and cellars. The multi-coat application process will self-prime and seal concrete and cinder blocks, masonry walls, stucco and brick. Sentinel Mold & Mildew Resistant Waterproofing Sealant's fungistatic agent resists mold and mildew growth on the dried coating surface.



Interior/Exterior / Low Odor

AVAILABLE IN A WHITE FINISH

INTERIOR & EXTERIOR USE

800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445

WHITE

FORMULA 24-7 ZERO WATERPROOFING SEALANT

Sentinel Mold & Mildew Resistant Waterproofing Sealant is a 100% acrylic water based, antimicrobial coating formulated to stop water penetration through masonry materials. For interior and exterior, above or below grade, vertical applications. Sentinel Mold & Mildew Resistant Waterproofing Sealant withstands 35 PSI of water pressure preventing moisture transmission into basements, crawlspaces and cellars. The multi-coat application process will self-prime and seal concrete and cinder blocks, masonry walls, stucco and brick. Sentinel Mold & Mildew Resistant Waterproofing Sealant's fungistatic agent resists mold and mildew growth on the dried coating surface.



Application Information (Always follow product label instructions for best results)

Independently Tested to Meet or Exceed ASTM Standards:

ASTM D7088

Negative Side Hydrostatic Pressure

ASTM C1306

Positive Side Hydrostatic Pressure

ASTM D6904-03(2022)

Standard Practice for Resistance to Wind-Driven Rain for Exterior Coatings Applied on Masonry

Surface Preparation:

Before applying Sentinel Mold & Mildew Resistant Waterproofing Sealant make sure all surfaces are clean, dry and free of loose contaminants. Any efflorescence present must be removed using a suitable chemical efflorescence remover or mechanical means. Loose paint must be removed. Fill any cracks and large holes with a hydraulic cement patching compound.

Product Application:

Stir thoroughly before using. 2 or more coats are required to ensure pinholes are filled to create a sound waterproof barrier. Apply 1st coat using a high quality synthetic bristle brush. Work the sealant into the pores and pinholes of the masonry. Allow the 1st coat to dry for 3 hours. 2nd coat can be applied using a brush, roller (3/8 - 1/2 inch nap), or spray application (.019 - .021 spray tip).

Product Application Continued:

Once the 2nd coat has dried examine the surface carefully for pinholes. These areas should be recoated. If using a sprayer to apply the 1st coat, backroll using a roller to fill any pinholes or voids. Apply additional coats as needed.

Coverage:

Applied at 7 mils wet per coat. 2 coats minimum (14 wet mils) required.
Smooth Surfaces: 125 Sq. Ft./Gallon
Porous Surfaces: 75-100 Sq. Ft./Gallon
Actual coverage may vary depending on application method, surface texture, and porosity.

Dry Time:

Dry to the touch in 1 hour. Recoat after 3 hours. Fully cured in 24 hours at 50% relative humidity or lower. 2 or more coats are required. 14 wet mils total between coats.

Thinner & Tinting:

Do NOT thin this product with mineral spirits, paint thinner or water. Sentinel Mold & Mildew Resistant Waterproofing Sealant is ready to use. Product may be tinted with universal colorant systems. Colorant loading limited to a maximum of 2 oz. per gallon. Can be tinted into light or pastel ranges only.

Clean Up:

Clean painting tools with warm soapy water while product is still wet. Any spills or splatters should be cleaned up immediately with a wet, soapy cloth. Dried coating may be removed using Sentinel 206 PeroxyStrip Paint and Coating Stripper or other commercially available paint strippers.

Storage & Application:

Store and apply in temperatures above 50°F. **This product must not be allowed to freeze.** In colder environments, bring product to room temperature before using.

Limitations:

This product does NOT protect users or others against foodborne or disease causing bacteria. This product is not designed to be used in areas with temperatures less than 50° F., excessive heat, corrosive chemical environments, or on exterior siding or high-traffic floor and deck areas. Avoid extended contact with solvent/petroleum based cleaners/degreasers/chemicals.

Properties:

Percent of Solids/Weight: 61.4%
Percent of Solids/Volume: 46.4%
Viscosity at 72°F: 110-125 Krebs Units
Gloss Level: Matte
Shelf Life: Unopened Container: 2 Years
VOC Content: < 5 g/L