

620 CARPET & SHEET VINYL ADHESIVE REMOVER CONCENTRATE

V.O.C. COMPLIANT

Sentinel 620 Carpet & Sheet Vinyl Adhesive Remover Concentrate is the complete product for easily removing indoor carpeting or for stripping the toughest latex and acrylic adhesives from all floor surfaces. 620 is a highly concentrated product designed to be diluted with hot water depending on the needs of the project.

Application Information (Always follow product label instructions for best results)

Review directions and precautions thoroughly before starting work.

USE CONDITIONS

This product works best at room temperature (70°F). Colder temperatures can affect product performance.

REMOVAL OF LATEX, ACRYLIC AND PRESSURE SENSITIVE ADHESIVES:

Step 1: Dilute 620. 4 parts HOT water to 1 part Sentinel 620.*

Step 2: Apply 620 mixture directly onto adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the surface wet. Allow mixture to soak and penetrate for 30-60 minutes.

Step 3: Scrape softened adhesive from the floor with a razor floor scraper. Repeat steps 2 and 3 if glue is especially thick or stubborn. Dispose of all waste following all local, state and federal regulations.

Step 4: Rinse the subfloor thoroughly with clean water. Allow surface to completely dry and test moisture levels before reflooring.

*For particularly tough adhesives, reduce the dilution ratio for a stronger solution.

REMOVAL OF SHEET VINYL OR LINOLEUM BACKING:

Once the wear layer is removed, mix 4 parts HOT water to 1 part 620. Apply directly to the backing and allow to soak through. Maintain even coverage and a wet surface for 1-2 hours or until backing and adhesive can easily be removed with a razor floor scraper. Rinse the surface with clean water and allow to dry. Test moisture levels before reflooring.

REMOVAL OF CARPETING:

Using a utility knife, cut the carpeting into strips 1 foot wide, making sure to cut all the way through to the subfloor. Mix 4 parts HOT water to 1 part 620 and pour directly onto carpet. Maintain even coverage and completely saturate carpeting. Allow to soak for 4 hours up to overnight. (If soaking overnight, covering the carpet with poly will help control evaporation and drying.) When carpet releases easily, roll up and remove. Follow latex removal steps to remove remaining adhesive.

WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

SPECIFICATIONS

Physical State:	Liquid
Appearance:	Clear
Color:	None
Odor:	Slight
pH:	11.0 - 12.0
Flash Point:	None to boiling
Boiling Point:	212°F
V.O.C. Content:	<45g/L (calc.)*
Shelf Life:	60 Months
Coverage Rate:	25 - 70 sq. ft./gal dependent on application

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445