PRODUCT DATA SHEET



747 PLUS ADHESIVE REMOVER

V.O.C. COMPLIANT

Sentinel 747 Plus Adhesive Remover is a powerful, biodegradable formula designed to safely and effectively strip adhesives left behind after removing vinyl tile, sheet vinyl, indoor carpeting, and wood flooring. 747 Plus is an environmentally friendly, low odor product that removes a variety of flooring adhesives without the use of harmful agents.

Application Information (Always follow product label instructions for best results) Review directions and precautions thoroughly before starting work.

USAGE GUIDELINES

This product works best at room temperature (70°F). Colder temperatures can affect product performance. Read Safety Data Sheet before use.

PREPARATION

Protect walls, cabinetry, trim, drains, cracks and ajoining flooring with plastic and/or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.

REMOVAL OF CUTBACK/MASTIC FOUND UNDER VINYL TILE AND PARQUE

Step 1: Wet the entire surface with 747 Plus. This may be done using a sprayer or mopping 747 Plus over the surface of the adhesive. Do not over apply 747 Plus in this first step. Allow the 747 Plus to soak and penetrate for 10-20 minutes to soften the adhesive. Scrape the bulk of the softened adhesive from the surface with a floor scraper and place in a disposable container.

Step 2: Reapply 747 Plus, this time working with smaller areas (approx. 4' X 4'). immediately agitate with a short bristled broom or floor scrubber to fully lift and liquefy adhesive residue from the sub floor. For easy clean up, add absorbent to the liquefied adhesive, place in a disposable container and dispose. Follow all local, state and federal regulations when disposing of waste.

Step 3: Wash and rinse the sub floor thoroughly with Sentinel 810 All Surface Floor Cleaner to ensure a clean surface. Allow surface to dry.

REMOVAL OF SHEET VINYL/LINOLEUM BACKING & INDOOR CARPET ADHESIVES

Coverage: Carpet= 25sq. ft./mixed gallon Sheet Vinyl Backing= 40 sq. ft./mixed gallon Latex Adhesive = 70 sq. ft./ mixed gallon

Step 1: Mix 1 part warm water to 1 part 747 Plus and apply mixture directly onto the adhesive/ backing. Use a broom or mop to agitate and maintain even coverage while keeping the adhesive surface wet. Allow 747 Plus to soak and penetrate for 60 - 90 minutes. Scrape the softened adhesive/ backing from the floor (razor scrapers are generally preferred) and put in a disposable container.

Step 2: Repeat step one if necessary. Add some absorbent to container and dispose. Follow all local, state and federal regulations when disposing of waste.

Step 3: Wash and rinse the sub floor thoroughly with Sentinel 810 All Surface Floor Cleaner to ensure a clean surface. Allow to dry.

REMOVAL OF CARPETING

Using a carpet cutter, cut the carpeting in 1'-3' foot strips. Mix 2 parts water to 1 part 747 Plus and pour directly onto carpet to be removed. Completely saturate carpeting with mixture and allow to soak a minimum of 2 hours. Remove carpeting and follow indoor carpeting adhesive removal directions.

WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any reponsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

SPECIFICATIONS

Physical State: Liquid Appearance: Clear

Color: None to amber

Odor: Low

pH: Not applicable

Flash Point: >170°F

Boiling Point: 363 -381°F

Self-Ignition Temp: 421°F

Vapor Pressure:<0.2 mm Hg@68°F</th>V.O.C. Content:<15g/L (calc.)*</th>Shelf Life:60 Months

Coverage Rate: 75 - 150 sq. ft./gal

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



800-373-0633 or www.senpro.com