PRODUCT DATA SHEET



787 ADHESIVE, SEAM & SPOT CLEANER

V.O.C. COMPLIANT

Sentinel 787 Adhesive, Seam & Spot Cleaner is a fast-acting, high-strength adhesive remover. It is specially formulated to remove adhesive spots and grease from carpets, vinyl, and wood flooring. Use to clean excess glue from carpet and vinyl floor seams as well as to clean and degrease metals.

Application Information (Always follow product label instructions for best results)

Review directions and precautions thoroughly before starting work.

USE CONDITIONS

This product works best at room temperature (70°F). Colder temperatures can affect product performance. Test in a small inconspicuous area to ensure color-fastness, particularly when using on carpet seams. Do not use if color transfers or is altered.

REMOVING SMALL GLUE SPOTS AND STAINS ON CARPETS OR WOOD FLOORS

Apply Sentinel 787 to a clean towel, rag or microfiber towel and wipe onto glue stain, haze or fingerprints. If glue has dried, allow 787 to penetrate and soften glue. Wipe spot until glue or stain is gone, removing all adhesive residue. Turn cloth frequently, using a clean area each time to wipe the stain or spot. Wipe any residue with warm soapy water. Allow floor to dry completely before walking

TO CLEAN VINYL FLOOR SEAMS

Apply 787 to a microfiber towel or clean rag and wipe seam clean. Wipe any 787 residue from floor with warm soapy water. Wipe dry.

TO REMOVE CARPET SEAM GLUE

Wipe seam with 787 on a clean rag or cloth to remove glue residue. Turn cloth frequently to expose clean areas for wiping. Wipe residue with clean cloth and warm soapy water. Allow to dry.

WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any reponsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

SPECIFICATIONS

Physical State: Liquid Appearance: Clear

Color: None to amber
Odor: Mild citrus
pH: Not applicable

Flash Point: >170°F Boiling Point: 363 - 381°F

Vapor Pressure:<0.5 mm Hg@68°F</th>V.O.C. Content:<50 g/L (calc.)*</th>Shelf Life:60 Months

Coverage Rate: 140 -200 sq. ft./gal

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



800-373-0633 or www.senpro.com