



811 MULTI-SURFACE ADHESIVE PRIMER

Sentinel 811 Adhesive Primer is a low odor, high performance primer designed to increase the adhesion of floor and wallpaper adhesives. Use prior to installing peel & stick (self-adhesive) tiles, wallpaper, and full spread adhesives used in the installation of sheet vinyl, carpet, carpet tiles, and paneling. Sentinel 811 can be used on most substrates, including plywood, OSB, and portland and gypsum-based building materials.

Application Information (Always follow product label instructions for best results)

Review directions and precautions thoroughly before starting work.

USAGE GUIDELINES

This product works best at room temperature (70°F). Do not use if the air temperature or temperature of the substrate is less than 50°F. This product is not intended for exterior use or as a general paint primer.

PREPARATION

Glossy/shiny surfaces should be scuffed with sandpaper before priming. All surfaces must be clean and dry before application of Sentinel 811 Multi-Surface Adhesive Primer.

STEP 1:

Shake or stir 811 prior to use. Product must NOT be reduced with water or solvents. 811 will appear milky white at application but will dry clear.

STEP 2:

811 may be applied with a brush, roller, or sprayer. Apply in a thin, uniform coat. Do not over apply in this step. Allow to dry completely. (30-60 minutes in ideal drying conditions.) Depending on the porosity of the substrate being primed, a second coat may be desired for optimal results.

STEP 3:

Apply second coat as needed and allow to dry. Second coat will take longer to dry than the first coat, so allow ample time for product to dry completely.

CLEAN UP:

Tools and equipment can be cleaned with soap and water while 811 is still wet.

WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

SPECIFICATIONS

Physical State:	Liquid
Appearance:	Opaque
Color:	Milky White
Odor:	Slight Acrylic Odor
pH:	7.0 - 8.0
Flash Point:	None to boiling
Boiling Point:	>212°F
Shelf Life:	36 Months
Coverage Rate:	200 - 400 sq. ft./gal depending on the porosity of the substrate



800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445