

840 SURFACTANT WETTING AGENT

Sentinel 840 Surfactant Wetting Agent is a superior wetting agent designed for use prior to the abatement of Asbestos Containing Materials (ACM). Sentinel 840 saturates fibers and lowers surface tension which aids in reducing the release of fibers and dust during removal.

Application Information (Always follow product label instructions for best results)

Review directions and precautions thoroughly before starting work.

USAGE GUIDELINES

Read directions and review Safety Data Sheet prior to use.

Always adhere to all regulations mandated by OSHA and EPA Guidelines when using this product in the removal of Asbestos Containing Materials (ACM).

Approved respirators and personal protective equipment must be used to prevent inhalation of airborne asbestos fibers.

Store in a dry locations with a temperature between 40°F and 90°F. Do not allow the product to freeze or the container may burst.

Dispose of all waste in accordance with all applicable local, state and federal regulations.

DILUTION

Sentinel 840 Surfactant Wetting Agent can be used at full strength or diluted.

If diluted, Sentinel 840 can be mixed with up to twenty (20) parts water to one (1) part Sentinel 840.

APPLICATION

Apply full strength or diluted product directly to the material with an airless sprayer or pump sprayer.

Air monitoring of fiber levels should be observed to determine when reapplication is necessary.

WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

SPECIFICATIONS

Physical State:	Liquid
Appearance:	Clear
Color:	None
Odor:	None
pH:	7.0 - 8.0
Flash Point:	None to boiling
Boiling Point:	212°F
Self-Ignition Temp:	28 Dynes/cm ²
Shelf Life:	60 Months



800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445