

922 URETHANE ADHESIVE REMOVER

V.O.C. COMPLIANT

Sentinel 922 Urethane Adhesive Remover is a low odor, biodegradable product designed to remove wet and recently cured urethane glues from pre-finished wood flooring, as well as facilitating the removal of damaged glued down wood floors.

Application Information (Always follow product label instructions for best results)

USE CONDITIONS

This product works best at room temperature (70°F). Colder temperatures can affect product performance.

PREPARATION

Protect walls, cabinetry, trim, drains, cracks and adjoining flooring with plastic and/or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.

REMOVING URETHANE ADHESIVES STEP 1:

Wet the entire adhesive surface with product. This may be done by using a garden sprayer or by applying 922 directly to the floor and using a mop or floor squeegee to move it over the surface of the adhesive. DO NOT overapply. Allow 922 to soak and penetrate for 30 - 60 minutes depending on the thickness of the adhesive.

STEP 2:

Scrape the bulk of the softened adhesive from the surface with a razor floor scraper. Place in a container for disposal.

STEP 3:

Reapply 922 and agitate with a short-bristled broom, hand held or rotating floor scrubber with stripper pads. Squeegee resulting mixture into puddles and solidify with an absorbent. Remove absorbed material to a container and dispose. Follow all local, state and federal regulations when disposing of waste.

STEP 4:

Wash and rinse the floor thoroughly using Sentinel 317 Multi-Purpose Cleaner and Degreaser and water or a soap and water solution. Allow subfloor to dry for at least 24 hours and test moisture levels before refinishing.

REMOVING GLUED DOWN WOOD FLOORING

STEP 1:

Using a circular saw set to the depth of the flooring, cut the flooring into 6" - 8" squares.

STEP 2:

Vacuum all sawdust from the cut lines and floor.

STEP 3:

Apply liberal amounts of 922 to the cut lines. Use a squeegee to distribute across the flooring. Allow 922 to soak and penetrate under the wood for 4 - 8 hours.

STEP 4:

Using a spade or similar tool, pry up old wood flooring. Squares should be intact and easy to remove. Once flooring is removed, follow directions at left for removing adhesive from subfloor.

WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

SPECIFICATIONS

Physical State:	Liquid
Appearance:	Clear
Color:	None to Amber
Odor:	Mild Musty Odor
pH:	Not applicable
Flash Point:	>200°F
Boiling Point:	470°F
Vapor Pressure:	<0.2 mm Hg@68°F
V.O.C. Content:	<500g/L (calc.)*
Shelf Life:	60 Months
Coverage Rate:	75 -200 sq. ft./gal Depending on application

This Specialty Adhesive Remover contains less than 70% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445