

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

170

LOW ODOR
FAST ACTING
GREATER COVERAGE

LOW ODOR MASTIC

REMOVER



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

5 Gallons (18.927L)



PRODUCT DESCRIPTION

SENTINEL 170 Low Odor Mastic Remover is designed to remove black asphalt cutback adhesives/mastic and rinse leaving no residue. When subfloors are dry, new flooring may be confidently installed. This material does NOT contain asbestos.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control user's handling, and use, or effect of that use.

WARNING

Sheet vinyl, vinyl or asphalt floor tiles and associated backings, mastics and other adhesives MAY contain asbestos, which is hazardous to health. Follow all local, state and federal regulations when removing adhesives containing asbestos.

DIRECTIONS

Review directions and precautions thoroughly before starting work.

STEP ONE: Protect walls, cabinetry, trim, drains, cracks and adjoining flooring with plastic and/or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.

DIRECTIONS CONTINUED

STEP TWO: Wet the entire adhesive surface with product. This may be done by using a garden sprayer or by applying 170 directly to the floor and using a mop or floor squeegee to move it over the surface of the adhesive. DO NOT overapply. Allow 170 to soak and penetrate for 10-20 minutes.
STEP THREE: Scrape the bulk of the softened adhesive from the surface with a floor scraper. This will help increase the coverage of 170 and reduce the amount of liquid generated and make final clean-up easier. Place in a container for disposal.
STEP FOUR: Reapply 170 as in Step One. To fully lift and liquify adhesive residue from the floor agitate with a short-bristled broom, hand held or rotating floor scrubber with stripper pads. Squeegee resulting mixture into puddles and solidify with an absorbent. Remove absorbed material to a container and dispose. Follow all local, state and federal regulations when disposing of waste.
STEP FIVE: Wash and rinse the floor thoroughly using Sentinel 317 Multi-Purpose Cleaner & Degreaser and water or a soap and water solution. Allow subfloor to dry for at least 24 hours and test moisture levels before reflooring.

DANGER



(Contains: Petroleum distillates, hydrotreated light, 2-(2-butoxyethoxy) ethanol, Surfactant)

HAZARD STATEMENTS: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks. No smoking. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. In case of fire: Use dry chemical, foam, CO2 extinction. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents /container to licensed waste handling facility.

FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition-No smoking. Keep only in the original container in a cool, well ventilated place away from: Heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

FOR SPECIAL INSTRUCTIONS CONTACT SENTINEL'S CUSTOMER SERVICE AT 1-800-373-0633 OR VISIT US AT www.senpro.com

FORMULA

170

LOW ODOR
FAST ACTING
GREATER COVERAGE



Sentinel Products, Inc.
Brooklyn Park, MN 55445
800-373-0633
www.senpro.com

