

FORMULA

24-7 PREMIUM

MOLD & MILDEW RESISTANT COATING

WHITE



Non-Harmful
Low VOCs*
Zero HAPs
Low Odor



Eco-Friendly
100% Acrylic
Water Based
Coating



Antimicrobial Protection
Inhibits Growth of Bacteria,
Mold & Mildew that cause
odors on the Cured Coating
Surface



For Use On:
Interior and exterior substrates including
wood, concrete, drywall, plaster, brick,
metal & painted surfaces

PRODUCT DESCRIPTION

SENTINEL 24-7 PREMIUM WITH ANTIMICROBIAL PRODUCT PROTECTION is an interior/exterior coating that represents a new generation of environmentally friendly products. 24-7 offers excellent hide, scrubability, flow, and leveling with virtually no odor. This product is designed for use on a variety of surfaces, including previously painted surfaces, wood, concrete, drywall, plaster, brick and most metals. This product is excellent for use in interior/exterior building applications, including office buildings, schools, apartments, hospitals, warehouses and homes.

LIMITED WARRANTY

Sentinel Products Inc. warrants this product to perform satisfactorily when used in accordance with label directions. Sentinel Products Inc. will replace the product or refund the purchase price in the event this product is proven defective, which shall be the exclusive remedy under the warranty. Liability for consequential damages is specifically excluded. No other warranties expressed or implied are given.

PRECAUTIONS

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

HEALTH & ENVIRONMENT

Titanium dioxide is considered hazardous as an airborne dust. During the use of 24-7 Premium these materials are bound within the product and do not present a significant risk of exposure. When 24-7 Premium has dried and cured, sanding or similar actions could create dust and subsequent exposure is possible. This product is lead free and mercury free. Safety Data Sheets are available upon request, or at www.senpro.com. When spraying, use suitable respiratory protection and provide adequate ventilation. Disposal of most latex paints is allowable in landfills if the material is in solid form. Always check local regulations before disposing of any product.



WARNING! This product can expose you to chemicals including Titanium Dioxide, which are known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov

WARNING



(Contains: Titanium dioxide)

HAZARD STATEMENTS: Suspected of causing cancer.

PRECAUTIONARY STATEMENTS: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye protection, protective clothing, protective gloves. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation develops and persists, seek medical attention. IF ON SKIN: Wash all exposed skin with soap and water for at least 15 minutes. If skin irritation develops and persists, seek medical attention. IF SWALLOWED: Rinse mouth thoroughly. Do NOT induce vomiting without advice from Poison Control Center or medical professional. Seek medical attention if you feel unwell. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If difficulties continue, seek medical attention.

HANDLING AND STORAGE: Wash hands thoroughly after handling. Keep container closed when not in use. Do not allow to freeze.

KEEP OUT OF REACH OF CHILDREN • REFER TO SDS FOR MORE INFORMATION

For special instructions or additional information contact Sentinel at: 800-373-0633 or visit us at www.senpro.com

FORMULA



INSTRUCTIONS

STORAGE & APPLICATION ENVIRONMENT

THIS PRODUCT MUST NOT BE ALLOWED TO FREEZE. Do not apply in temps. below 50°F. In colder environments, bring product up to normal room temperature before using. This product has a 3 year shelf life.

SURFACE PREPARATION & PRIMING

All surfaces must be clean and dry. Remove any dirt or peeling paint. Spackle and sand where necessary. Lightly sand all glossy areas. Wash or clean oily or dirty surfaces with a suitable cleaning compound and rinse before painting and allow to dry. On new sanded sheetrock surfaces remove all sanding dust before painting. In new construction sheetrock and masonry must be allowed to fully cure before coating.

APPLICATION

Stir contents thoroughly. Apply with a nylon or polyester brush. This product may also be applied using a roller, pad or airless sprayer (using a .015 - .019 tip). Do not brush out excessively and allow product to flow on. Keep a wet edge, not allowing paint to dry in the middle of the wall. This will help avoid lap marks and assure proper coverage.

COVERAGE

On smooth surfaces, approximately 300-400 sq. ft. of coverage per gallon. Expect slightly less coverage on rough surfaces. Actual coverage may vary depending upon application method, surface texture, and porosity.

DRY TIME

Dry to the touch in 1 hour. Fully cured in 24 hours at 75°F 50% relative humidity or lower. 2 or more coats may be required. 6-9 wet mils total between coats. This latex product may be recoated in 2 hours under most environmental conditions. Allow for longer drying times in areas of high humidity or dampness.

THINNER & TINTING

Do NOT thin this product with mineral spirits or paint thinner. 24-7 Premium is ready to use. Product may be tinted with universal colorant systems. Colorant loading to a maximum of 4 oz. per gallon and limited to pastel colors.

CLEAN UP

Clean painting tools with warm soapy water while product is still wet. Any spills or splatters should be cleaned up immediately with a wet, soapy cloth. Dried coating may be removed using Sentinel 206 Peroxy Strip Paint and Coatings Stripper or other commercially available paint strippers.

