

FORMULA

532

Solvent Based
Ready To Use

THERMAL FOGGING SMOKE & ODOR COUNTERACTANT



PRODUCT DESCRIPTION

Sentinel 532 Thermal Fogging Smoke & Odor Counteractant is a professional strength odor control product used to eliminate odors commonly associated with restoration projects like smoke odor and damp musty odors. Sentinel 532 is designed to be used in thermal fogging applications.

WARRANTY NOTICE

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.



DANGER

(Contains: Petroleum distillates, hydrotreated light, Proprietary Fragrance Blend)

HAZARD STATEMENTS: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause allergic reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
PRECAUTIONARY STATEMENTS: Keep away from heat, open flames, sparks.-No smoking. Avoid breathing mist/ vapors/spray. Use only outdoors or in a well ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/ attention. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. If swallowed, do NOT induce vomiting. **IF INHALED:** Remove victim to fresh air and kkeep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. Avoid release to the environment. Collect spillage. In case of fire: Use dry chemical, foam, CO2 for extinction. Store in a well -ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container to licensed waste handling facility.
FIRST AID: **IF INHALED:** If breathing difficulties, dizziness or light headedness occur when working in areas with high vapor concentration, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing stops, begin artificial and seek immediate medical attention. **IF ON SKIN:** Remove contaminated clothing. Immediately rinse with plenty of mild soap and water (for at least 15 minutes). If skin irritation occurs: get medical advice/attention. **IF IN EYES:** Rinse immediately and thoroughly, pulling eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation occurs, get medical advice/attention. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor physician. Do NOT induce vomiting. Obtain emergency medical attention.
HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN**
REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY

USAGE GUIDELINES

Read directions thoroughly prior to use. Take measures to minimize exposure to potentially sensitive individuals. Turn off pilot lights and any other potential sources of ignition. Clear the treatment area of individuals, pets and cover or remove items such as food, utensils and other items affected by petroleum solvents. Test in small inconspicuous area prior to using on soft goods and fabrics to assure desired results.

DIRECTIONS FOR USE

Do NOT dilute Sentinel 532. Apply with thermal fogging device apparatus ONLY.

- 1) Issue respirators to individuals involved in application
- 2) Apply Sentinel 532 at a rate of 1 ounce per 1,000 cubic feet of airspace.
- 3) Keep doors and windows closed and area vacated for a minimum of 30 minutes after fogging.
- 4) Ventilate area prior to re- entry and re - occupancy.

FORMULA

532

Solvent Based
Ready To Use

FOR SPECIAL INSTRUCTIONS CONTACT
SENTINEL'S CUSTOMER SERVICE AT 1.800.373.0633
OR VISIT US AT www.senpro.com



Sentinel Products Inc.
Minneapolis, MN 55445
800-373-0633
www.senpro.com