

FORMULA

540

Odor Encapsulating
Fresh Scent
Water Based
ZERO V.O.C.'s

DRY FALL
COATING

WHITE



PRODUCT DESCRIPTION

Sentinel 540 Dry Fall Coating is a fast-drying product designed for high ceiling applications. 540 provides good light reflectancy. 540 contains odor encapsulating and odor counteracting properties for trapping and covering up smoke and other odors. When sprayed on ceiling heights of 15' or more, overspray will usually dry before reaching the floor and can be vacuumed or swept up.

WARRANTY NOTICE

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.

WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

USAGE GUIDELINES

For best results, mix thoroughly before use. Designed for use on ceilings higher than 15'. Do not use on floors or walls in high traffic areas, in high temperature applications or in water immersion. FOR INTERIOR USE ONLY. DO NOT USE OVER UNPRIMED METAL SURFACES. If priming is necessary, use Sentinel Stain Blocking Primer. Use on steel roofing, brick, concrete, wood, plaster, drywall or similar substrates.

Surface Preparation: Remove all loose old paint and clean surfaces of all dirt, dust, oil, grease, wax, rust, or other contaminates. Allow all new masonry surfaces, plaster or drywall to cure before coating.

Application: DO NOT THIN. Apply in an environment greater than 50°F and less than 50% relative humidity. Apply by spray application only. Tip size .015-.021. Do not brush or roll. When spraying keep gun close to surface so coating does not dry before reaching the substrate being coated.

Dry Time: Dries to the touch in 30 minutes at 77°F and 50%RH. Allow one hour before recoating.

Coverage: Porous Surfaces: 75-250 sq. ft./gallon. **Non-Porous Surfaces:** 125-300 sq. ft./gallon. Varies greatly on different surfaces and does not include spray loss.

Tinting: Sentinel 540 Dry Fall Coating may be tinted with up to 2 oz. of colorant per gallon. **Clean -Up:** Warm soapy water.

HEALTH & ENVIRONMENT

Use approved respirators and provide adequate ventilation when spraying this product. This material is lead free, mercury free and formaldehyde free. Titanium Dioxide and Crystalline Silica are considered hazardous as an airborne dust. During the use of this product these materials are bound within the coating and do not present a serious risk of exposure. Once this product has cured, sanding or similar actions could create dust and subsequent exposure is possible. Disposal of most latex paints is allowable in landfills, if the material is in solid form. Always check local regulations before disposing of any product. Close container when not in use. Store and transport in an upright position. KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.

*NOTICE

A zero v.o.c. coating by industry standards means the product contains fewer than 5 grams of v.o.c.'s per liter. Tints and colorants may add v.o.c.'s to the product.



WARNING. This product can expose you to chemicals including Titanium Dioxide, which are known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



WARNING
(Contains: Titanium dioxide, Calcium Carbonate, Crystalline Silica)

HAZARD STATEMENTS: May cause cancer (Inhalation of dust). May cause damage to lungs through prolonged and repeated exposure to dust.

PRECAUTIONARY STATEMENTS: Do not breathe dust. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. If exposed or concerned: get medical advice. Get medical advice/attention if you feel unwell. Store locked up. Dispose of contents/container to licensed waste handling facility.

FIRST AID: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking or irritation develops or persists, get medical attention. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Move person to fresh air. IF SWALLOWED: Rinse mouth. Seek medical attention.

HANDLING AND STORAGE: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep container closed when not in use. Keep from freezing. Refer to SDS for more information. KEEP OUT OF REACH OF CHILDREN.

FORMULA

540

Odor Encapsulating
Fresh Scent
Water Based
ZERO V.O.C.'s

FOR SPECIAL INSTRUCTIONS CONTACT
SENTINEL'S CUSTOMER SERVICE AT 1.800.373.0633
OR VISIT US AT www.senpro.com



Sentinel Products, Inc.
8901 Wyoming Ave. N.
Brooklyn Park, MN 55445
800-373-0633
www.senpro.com

