

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

620

BIODEGRADABLE
LOW ODOR FORMULA
HIGHLY CONCENTRATED
EASILY REMOVES:
GLUED DOWN CARPET
SHEET VINYL
CARPET FOAM BACKING

CARPET & SHEET VINYL ADHESIVE REMOVER CONCENTRATE



PRODUCT DESCRIPTION

SENTINEL 620 CARPET & SHEET VINYL ADHESIVE REMOVER CONCENTRATE is the complete product for easily removing carpeting or for stripping the toughest latex and acrylic adhesives from all floor surfaces. 620's unique formula works quicker, cleans and removes better and is easier to use than all other remover products.

USAGE GUIDELINES

For best results use at room temperature and read instructions before using. Coverage rates will vary based upon the thickness and quality of the adhesive being removed as well as the room temperature.

WARNING

Sheet vinyl, vinyl or asphalt floor tiles and associated backings, mastics and other adhesives MAY contain asbestos, which is hazardous to health. Follow all local, state and federal regulations when removing materials containing asbestos.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price because seller cannot control user's handling, and use, or effect of that use.

DIRECTIONS

While 620 works on most latex, acrylic, and pressure sensitive adhesives, it is recommended that you test a small area first.

REMOVAL OF CARPETING

Using a utility knife, cut the carpeting into 1-foot strips (making sure to cut through the carpeting to the subfloor). Mix 4 parts HOT water to 1 part SENTINEL 620 (e.g. 4 gallon HOT water to 1 gallon 620) and pour directly onto carpet to be removed. Depending on the nature of the carpet to be removed, coverage of about 35 square feet per gallon should be achieved. Allow to soak for 4 hours to overnight. (If soaking overnight, covering with poly is recommended.) Pull up carpet strips. Scrape softened glue. Rinse with hot water and allow to dry before reflooring. (If you cannot scrape all the way down to the subfloor after removing the carpeting, follow adhesive removal directions below.)

REMOVAL OF LATEX, ACRYLIC AND PRESSURE-SENSITIVE ADHESIVES

STEP ONE: Apply diluted 620 (4 parts HOT water to 1 part 620) directly to the adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the adhesive surface wet. Allow to soak and penetrate the adhesive for 20-75 minutes.

STEP TWO: Agitate with a stiff broom or stripper pads and scrape softened adhesive from the floor with a scraper (razor scrapers or squeegees are generally preferred). Repeat steps one and two if necessary and dispose of the waste.

STEP THREE: Rinse the sub-floor thoroughly with clean water. Allow the surface to dry completely before reflooring.

REMOVAL OF SHEET VINYL/LINOLEUM BACKING

Once the wear layer is removed, mix 4 parts HOT water to 1 part SENTINEL 620 (e.g. 4 gallons HOT water to 1 gallon 620) and apply directly to remaining backing. Maintain even coverage and wet surface for 1-2 hours or until the backing and adhesive can be easily removed together. Agitate adhesive residue with a stiff broom or stripper pads and remove with a floor scraper. Rinse the surface with clean water. Allow to dry completely before reflooring.



HAZARD

(Contains: 2-aminoethanol, 2-(2-butoxyethoxy) ethanol, Surfactant)

HAZARD STATEMENTS: Causes skin irritation. Causes serious eye damage.

PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

ADDITIONAL FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth, do NOT induce vomiting. Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking, and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep only in the original container in a cool, well ventilated place away from: Heat sources. Keep container closed when not in use.

FOR INDUSTRIAL USE ONLY REFER TO SDS FOR MORE INFORMATION KEEP OUT OF REACH OF CHILDREN

FOR SPECIAL INSTRUCTIONS CONTACT SENTINEL'S CUSTOMER SERVICE AT 1-800-373-0633 OR VISIT US AT www.senpro.com



5 Gallons (18.927L)

