

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

626

LOW ODOR
NON FLAMMABLE
WATER BASED

CARPET & SHEET VINYL ADHESIVE

REMOVER



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

5 Gallons (18.927L)



PRODUCT DESCRIPTION

SENTINEL 626 CARPET & SHEET VINYL ADHESIVE REMOVER is a powerful, biodegradable formulation designed specifically for quickly removing latex, acrylic and pressure sensitive adhesives from concrete, terrazo, ceramic and vinyl tile or wood substrates.

USAGE GUIDELINES

For best results use at room temperature and read instructions before using. Coverage rates will vary based upon the thickness and quality of the adhesive being removed as well as the room temperature.

WARNING

Sheet vinyl, vinyl or asphalt floor tiles and associated backings, mastics and other adhesives MAY contain asbestos, which is hazardous to health. Follow all local, state and federal regulations when removing materials containing asbestos.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price because seller cannot control user's handling, and use, or effect of that use.

DIRECTIONS

FOR BEST RESULTS: Open container and fill remaining space in pail with HOT water before applying. Calculate coverage at 70 sq. ft. per gallon. NOTE: Coverage rates will vary based upon the thickness and quality of adhesive being removed as well as room temperature.

REMOVAL OF LATEX, ACRYLIC AND PRESSURE-SENSITIVE ADHESIVES

STEP ONE: Apply SENTINEL 626 directly to the adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the adhesive surface wet. Allow SENTINEL 626 to soak and penetrate the adhesive for 45-90 minutes.

STEP TWO: Agitate with a stiff broom or stripper pads and scrape softened adhesive from the floor with a scraper (razor scrapers or squeegees are generally preferred). Repeat steps one and two if necessary and dispose of the waste.

STEP THREE: Rinse the sub-floor thoroughly with clean water. Allow the surface to dry completely before reflooring.

REMOVAL OF SHEET VINYL/LINOLEUM BACKING

Once the wear layer is removed, mix 1 part HOT water to 4 parts SENTINEL 626 (e.g. 1 quart HOT water to 1 gallon 626) and apply directly to remaining backing. Maintain even coverage and wet surface for 1-2 hours or until the backing and adhesive can be easily removed together. Agitate adhesive residue with a stiff broom or stripper pads and remove with a floor scraper. Rinse the surface with clean water. Allow to dry completely before reflooring.

REMOVAL OF CARPETING

Using a utility knife, cut the carpeting into 1-foot strips (making sure to cut through the carpeting to the subfloor). Mix 1 part HOT water to 1 part SENTINEL 626 (e.g. 1 gallon HOT water to 1 gallon 626) and pour directly onto carpet to be removed at a rate of 30 sq. ft. per gallon. Maintain even coverage and completely saturate the carpet with SENTINEL 626. Allow to soak for 4 hours to overnight. Pick up carpet strips and follow latex removal procedures above.



DANGER

(Contains: 2-aminoethanol, 2-(2-butoxyethoxy) ethanol, Surfactant)

HAZARD STATEMENTS: Causes skin irritation. Causes serious eye damage.

PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

ADDITIONAL FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth, do NOT induce vomiting. Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking, and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep only in the original container in a cool, well ventilated place away from: Heat sources. Keep container closed when not in use.

FOR INDUSTRIAL USE ONLY REFER TO SDS FOR MORE INFORMATION KEEP OUT OF REACH OF CHILDREN

FOR SPECIAL INSTRUCTIONS CONTACT SENTINEL'S CUSTOMER SERVICE AT 1-800-373-0633 OR VISIT US AT www.senpro.com

FORMULA

626

LOW ODOR
NON FLAMMABLE
WATER BASED



Sentinel Products, Inc.
Brooklyn Park, MN 55445
800-373-0633
www.senpro.com

