

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

F O R M U L A

7200

NO ODOR  
FASTER ACTING  
GREATER COVERAGE  
OVER 200° FLASH

# NO ODOR/200° FLASH MASTIC REMOVER



This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

5 Gallons (18.927L)



### PRODUCT DESCRIPTION

**SENTINEL 7200 NO ODOR/200 FLASH MASTIC REMOVER** is a high flash stripping solution designed to remove asphalt cutback adhesives and rinse leaving no residue. When subfloors are dry new flooring may be confidently installed.

### WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond the purchase price because seller cannot control users handling, and use, or effect of that use.

### DIRECTIONS

#### BLACK CUTBACK ADHESIVE REMOVAL

**STEP ONE:** Protect walls, cabinetry, trim, drains, cracks and adjoining flooring with plastic and/or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.  
**STEP TWO:** Wet the entire adhesive surface with 7200. This may be done by using a garden sprayer or by mopping 7200 over the surface of the adhesive. DO NOT overapply. Allow 7200 to soak and penetrate for 10-20 minutes.  
**STEP THREE:** Scrape the bulk of the softened adhesive from the surface with a floor scraper (8 inch razor scraper generally preferred). This will help increase the coverage of 7200 and reduce the amount of liquid generated. Place in a container for disposal.  
**STEP FOUR:** Reapply 7200 as in step one. Agitate with a short-bristled broom, hand-held or rotating floor scrubber with stripper pads to fully lift and liquify adhesive residue from the subfloor. Squeegee the resulting mixture into puddles and solidify with an absorbent. Remove absorbed material to a container and dispose. Follow all local, state and federal regulations when disposing of waste.  
**STEP FIVE:** Wash and rinse the floor thoroughly using Sentinel 317 Multi-Purpose Cleaner & Degreaser and water or a soap and water solution. Allow subfloor to dry for at least 24 hours and test moisture levels before reflooring.



### DANGER

(Contains: Petroleum distillates, hydrotreated light, 2-(2-butoxyethoxy) ethanol, Surfactant) May be fatal if swallowed and enters airways.

**HAZARD STATEMENTS:** May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.  
**PRECAUTIONARY STATEMENTS:** Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. If swallowed, do NOT induce vomiting. Store locked up. Dispose of contents/container to licensed waste handling facility.  
**FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS: IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.  
**HANDLING AND STORAGE:** Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - no smoking. In case of fire: Use dry chemical, foam, CO2 extinction. Keep only in the original container in a cool, well ventilated place away from: heat sources. Keep container closed when not in use.

REFER TO SDS FOR MORE INFORMATION • FOR INDUSTRIAL USE ONLY • KEEP OUT OF REACH OF CHILDREN

FOR SPECIAL INSTRUCTIONS CONTACT SENTINEL'S CUSTOMER SERVICE AT 800.373.0633 OR VISIT US AT [www.senpro.com](http://www.senpro.com)

F O R M U L A

7200

NO ODOR  
FASTER ACTING  
GREATER COVERAGE  
OVER 200° FLASH



Sentinel Products Inc.  
Brooklyn Park, MN 55445  
800-373-0633  
[www.senpro.com](http://www.senpro.com)

