

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA
811

MULTI-SURFACE ADHESIVE PRIMER

PERFECT FOR:

WOOD, CONCRETE, VINYL,
PAINTED SURFACES, PLYWOOD,
DRYWALL, PARTICLE BOARD

ENHANCES BONDING ABILITY
OF ADHESIVES

USE BEFORE APPLYING WALL
OR FLOORING ADHESIVES

LOW ODOR
FAST DRYING FORMULA



1 GALLON (3.79L)

CAUTION: MAY CAUSE EYE AND SKIN
IRRITATION ON CONTACT.
Read precautions on back panel.

SENTINEL 811 Multi-Surface Adhesive Primer is a low-odor, high-performance primer, designed to increase the adhesion of new flooring and wall adhesives. Use 811 prior to the installation of new interior floor & wall coverings to prime the surface and improve the adhesion of these items to sub-floors and walls. 811 is strongly recommend for use prior to installing self-adhesive tiles.

USAGE GUIDELINES:

Sentinel 811 is not intended for exterior use. 811 will improve the bonding ability of new adhesives when used on plywood, particle board, wood, concrete, terrazzo, brick, masonry, stone, ceramic, drywall, plaster, metal, and **finished floors*** (vinyl tile, sheet vinyl, painted surfaces). Substrate to be primed should be clean, free of any loose debris and dry. **Coverage rates will vary based on the porosity of the substrate being primed but will average @ 300 square feet per gallon.** For best results, do NOT dilute or thin Sentinel 811 with solvents or water. 811 will be milky white when applied and dry clear and dry to the touch.

***When applying 811 on finished flooring - Any sealers, coatings or waxes should be stripped or removed prior to applying 811 to allow for better adhesion. 811 may take longer to dry on these surfaces as well.**

Directions for Use:

1. Clean surfaces with Sentinel 810 All-Surface Floor Cleaner before applying 811. All surfaces must be clean and completely dry before application. Use only when temperature is above 50°F.
2. Shake or stir 811 thoroughly prior to use. Product must not be reduced with water or solvents.
3. Apply 811 using a sprayer, brush or roller. Apply in a thin, uniform coat. Do not overapply.
4. Allow 811 to dry thoroughly (approximately 30-60 minutes). Drying times will vary based upon humidity and temperature. For optimal results, apply a second coat once first coat is dry. Allow second coat to dry completely before applying new coverings. You can wait to apply new flooring but should avoid tracking dirt and debris onto the dried primer surface. Once completely dry, primed surfaces can be dry-wiped or vacuumed prior to applying new flooring or adhesive.

Clean-Up:

Brushes, rollers, or spray equipment may be cleaned (while 811 is still wet) with soap and water.

FOR USAGE QUESTIONS OR ADDITIONAL INFORMATION, CONTACT SENTINEL CUSTOMER SERVICE AT 1-800-373-0633 OR VISIT US ON THE WEB AT www.senpro.com.

CAUTION: KEEP OUT OF REACH OF CHILDREN. May cause eye and skin irritation. Keep container closed when not in use. Store and transport in upright position. **KEEP FROM FREEZING.**

FIRST AID: If taken internally, do NOT induce vomiting and call physician immediately. In case of eye contact, flush thoroughly with water and seek medical attention. For skin contact, wash thoroughly with soap and water.

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.



V.O.C. content less than 1 g/L



Manufactured by: Sentinel Products Inc.

8901 Wyoming Avenue North, Brooklyn Park, MN 55445, 1-800-373-0633