

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

FORMULA

922

SIMPLE 4 STEP PROCESS
EASILY REMOVES:
URETHANE
SOLVENT AND
ACRYLIC BASED ADHESIVES

REMOVES CURED
URETHANES

BIODEGRADABLE
LOW ODOR FORMULA

CAUTION: EYE IRRITANT.
Carefully read and follow directions and cautions on
back panel. KEEP OUT OF REACH OF CHILDREN.

Sentinel
Products Inc.™
BETTER SOLUTIONS FOR A CLEANER ENVIRONMENT

URETHANE ADHESIVE
REMOVER

PRODUCT DESCRIPTION

SENTINEL® 922™ URETHANE ADHESIVE REMOVER is a low odor and readily biodegradable solution. 922 is specially formulated for cleaning all wood adhesives including urethane and is water rinsable. It is recommended that you test a small area first.

WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond the purchase price, because seller cannot control user's handling, and use, or effect of use.



WARNING

(Contains: Soy Methyl Ester, Aliphatic dibasic esters, 2-(2-butoxyethoxy)ethanol, Surfactant

HAZARD STATEMENTS: Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: get medical advice/attention. Dispose of contents/container to licensed waste handling facility.

FIRST AID: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if unwell. IF ON SKIN: Immediately rinse with plenty of soap and water (for at least 15 minutes). Take off contaminated clothing and wash before reuse. If irritation persists: Get medical advice/attention. IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum) Remove contact lenses, if present and easy to do so. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Obtain emergency medical attention.

HANDLING AND STORAGE: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition- No Smoking. Keep only in the original container in a cool, well ventilated place away from: Heat sources. Close container when not in use.

REFER TO SDS FOR MORE INFORMATION FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

INSTRUCTIONS FOR USE

While 922 works on most cured urethane adhesives, it is strongly recommended to clean and remove urethanes before they are fully cured.

FOR SPOT CLEANING URETHANE FROM NEWLY INSTALLED WOOD FLOORS:

STEP ONE: Apply 922 to the spot either by using a rag or pouring directly onto spot. Allow to soak for 1 hour.
STEP TWO: Using a plastic putty knife, gently remove the softened adhesive.
STEP THREE: Wipe excess 922 from floor and wash entire floor with **Sentinel 810 All Surface Floor Cleaner**.

Note: Be sure **NOT** to scrub the surface of the finished wood too aggressively as this will change the look of the finish.

FOR REMOVING WOOD ADHESIVES:

STEP ONE: Wet the entire adhesive surface with 922. This may be done by using a sprayer or by mopping 922 over the surface of the adhesive. Do not over apply the 922. Allow the 922 to soak and penetrate for 30-60 minutes depending on the thickness of the adhesive.

STEP TWO: Scrape the bulk of the softened adhesive from the surface with a floor scraper (razor scrapers are generally preferred).

STEP THREE: If necessary, protect walls, drains, cracks and other flooring with an absorbent. Liquefied Adhesive can be absorbed using kitty litter, sawdust, etc. and removed. Follow the above three steps again if residual adhesives need to be removed.

STEP FOUR: Wash and rinse floor thoroughly with **Sentinel 810™** and water to ensure a clean surface. Allow to dry.

FOR REMOVAL OF GLUED DOWN WOOD FLOORING:

STEP ONE: Cut the wood surface using a circular saw into 6-8" by 6-8" square blocks. Set the saw to cut through the wood flooring down to the subfloor being careful not to cut into subfloor.

STEP TWO: Vacuum sawdust off of floor and out of cut lines.
STEP THREE: Apply 922 liberally to surface using a squeegee or mop making sure that all of the 922 product penetrates the cut line. Typical coverage will be ~ 75 square feet per gallon. Allow the product to soak and penetrate under the wood for 4-8 hours.

STEP FOUR: Using a spade or similar tool, pry up old wood flooring. Squares should be intact and easy to remove with little effort. Follow the above four steps for removal of adhesive from subfloor.

FORMULA

922

LOW ODOR
BIODEGRADABLE

For special instructions or additional information,
contact Sentinel's Customer Service at 800.373.0633
or Internet: <http://www.senpro.com>.

5 Gallons (18.927L)

Sentinel
Products Inc.™
BETTER SOLUTIONS FOR A CLEANER ENVIRONMENT

Sentinel Products Inc.
Minneapolis, MN 55445
800-373-0633
www.senpro.com

